



LY3N-D2 DC24 Information



For Reference Only

Part Number LY3N-D2 DC24

Manufacturer Omron Automation and Safety

Category Relays

Power Relays, Over 2 Amps

Description RELAY GEN PURPOSE 3PDT 10A 24V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









LY3N-D2 DC24 Specifications

Manufacturer Part Number LY3N-D2 DC24 Manufacturer Omron Automation and Safety Category Relays Power Relays, Over 2 Amps Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 58.6mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In		
CategoryRelaysPower Relays, Over 2 AmpsPackage-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current58.6mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer Part Number	LY3N-D2 DC24
Package-SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current58.6mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Manufacturer	Omron Automation and Safety
Package - Series LY Relay Type General Purpose Coil Type Non Latching Coil Current 58.6mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Category	Relays
SeriesLYRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current58.6mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In		Power Relays, Over 2 Amps
Relay Type General Purpose Coil Type Non Latching Coil Current 58.6mA Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Package	-
Coil TypeNon LatchingCoil Current58.6mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Series	LY
Coil Current58.6mACoil Voltage24VDCContact Form3PDT (3 Form C)Contact Rating (Current)10ASwitching Voltage250VAC, 125VDC - MaxTurn On Voltage (Max)19.2 VDCTurn Off Voltage (Min)2.4 VDCOperate Time25msRelease Time25msFeaturesLED IndicatorMounting TypeSocketableTermination StylePlug In	Relay Type	General Purpose
Coil Voltage 24VDC Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Type	Non Latching
Contact Form 3PDT (3 Form C) Contact Rating (Current) 10A Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style Plug In	Coil Current	58.6mA
Contact Rating (Current) Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Release Time LED Indicator Mounting Type Socketable Termination Style	Coil Voltage	24VDC
Switching Voltage 250VAC, 125VDC - Max Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Contact Form	3PDT (3 Form C)
Turn On Voltage (Max) 19.2 VDC Turn Off Voltage (Min) 2.4 VDC Operate Time 25ms Release Time 25ms LED Indicator Mounting Type Socketable Termination Style 19.2 VDC LED Indicator	Contact Rating (Current)	10A
Turn Off Voltage (Min) Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Switching Voltage	250VAC, 125VDC - Max
Operate Time 25ms Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn On Voltage (Max)	19.2 VDC
Release Time 25ms Features LED Indicator Mounting Type Socketable Termination Style Plug In	Turn Off Voltage (Min)	2.4 VDC
Features LED Indicator Mounting Type Socketable Termination Style Plug In	Operate Time	25ms
Mounting Type Socketable Termination Style Plug In	Release Time	25ms
Termination Style Plug In	Features	LED Indicator
	Mounting Type	Socketable
Report errors?	Termination Style	Plug In
		Report errors?

LY3N-D2 DC24 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

LY3N-D2 DC24 Payment Methods



















LY3N-D2 DC24 Shipping Methods













If you have any question about LY3N-D2 DC24, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com