

M12D-04PMMS-SF8001

M12D-04PMMS-SF8001 Information



For Reference Only

Part Number M12D-04PMMS-SF8001

Manufacturer Amphenol LTW

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG MALE 4POS GOLD SOLDER

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M12D-04PMMS-SF8001 Specifications

Manufacturer Part Number M12D-04PMMS-SF8001 Manufacturer Amphenol LTW Category Connectors, Interconnects Package - Series M Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A		
CategoryConnectors, InterconnectsPackage-SeriesMConnector TypePlug, Male PinsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationDIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeaturesShieldedVoltage - Rated250VCurrent Rating4A	Manufacturer Part Number	M12D-04PMMS-SF8001
Package-SeriesMConnector TypePlug, Male PinsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationDIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeaturesShieldedVoltage - Rated250VCurrent Rating4A	Manufacturer	Amphenol LTW
Package-SeriesMConnector TypePlug, Male PinsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationDIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeaturesShieldedVoltage - Rated250VCurrent Rating4A	Category	Connectors, Interconnects
SeriesMConnector TypePlug, Male PinsNumber of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationDIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeaturesShieldedVoltage - Rated250VCurrent Rating4A		Circular Connectors
Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert M12-4 Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Package	-
Number of Positions4Shell Size - InsertM12-4Shell Size, MIL-Mounting TypePanel Mount, Bulkhead - Front Side NutTerminationSolder CupFastening TypeThreadedOrientationDIngress ProtectionIP68/69K - Dust Tight, Water Resistant, WaterproofShell Material, FinishPolyamide (PA), Nylon, Glass FilledContact FinishGoldFeaturesShieldedVoltage - Rated250VCurrent Rating4A	Series	M
Shell Size - Insert Shell Size, MIL - Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated Current Rating 4A	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Panel Mount, Bulkhead - Front Side Nut Solder Cup Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated Current Rating 4A	Number of Positions	4
Mounting Type Panel Mount, Bulkhead - Front Side Nut Termination Solder Cup Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Shell Size - Insert	M12-4
Termination Solder Cup Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Shell Size, MIL	-
Fastening Type Threaded Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Mounting Type	Panel Mount, Bulkhead - Front Side Nut
Orientation D Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Termination	Solder Cup
Ingress Protection IP68/69K - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Fastening Type	Threaded
Shell Material, Finish Polyamide (PA), Nylon, Glass Filled Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Orientation	D
Contact Finish Gold Features Shielded Voltage - Rated 250V Current Rating 4A	Ingress Protection	IP68/69K - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated 250V Current Rating 4A	Shell Material, Finish	Polyamide (PA), Nylon, Glass Filled
Voltage - Rated 250V Current Rating 4A	Contact Finish	Gold
Current Rating 4A	Features	Shielded
-	Voltage - Rated	250V
Report errors?	Current Rating	4A
		Report errors?

M12D-04PMMS-SF8001 Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M12D-04PMMS-SF8001 Payment Methods



















M12D-04PMMS-SF8001 Shipping Methods













If you have any question about M12D-04PMMS-SF8001, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com