

M16-JA-5D Information

Heisener.com

Part Number M16-JA-5D

Manufacturer Omron Automation and Safety

Category Optoelectronics

Panel Indicators, Pilot Lights

Description PILOT LIGHT 5V LED RECT BLUE

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M16-JA-5D Specifications

Manufacturer Part Number M16-JA-5D Manufacturer Omron Automation and Safety Category Optoelectronics Panel Indicators, Pilot Lights Package - Series M16 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Diffused Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features - Report errors?		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series M16 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Diffused Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Manufacturer Part Number	M16-JA-5D
Package - Series M16 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Diffused Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Ingress Protection IP40 Features - Series M16 M16 M16 M16 M16 M16 M16 M16	Manufacturer	Omron Automation and Safety
Package - Series M16 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Diffused Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Category	Optoelectronics
Series M16 Type LED Lamp Color Blue Lens Color Blue Lens Transparency Diffused Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorBlueLens ColorBlueLens TransparencyDiffusedRatingsDCVoltage5VCurrent8mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRectangle with Flat Top, 21.00mm x 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP40Features-	Package	-
Lamp Color Lens Color Blue Lens Transparency Diffused Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak Viewing Angle Termination Style Ingress Protection Panel Cutout Dimensions I P40 Features Blue Blue Blue Blue Blue Blue Blue Blu	Series	M16
Lens ColorBlueLens TransparencyDiffusedRatingsDCVoltage5VCurrent8mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRectangle with Flat Top, 21.00mm x 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP40Features-	Type	LED
Lens TransparencyDiffusedRatingsDCVoltage5VCurrent8mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRectangle with Flat Top, 21.00mm x 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP40Features-	Lamp Color	Blue
Ratings DC Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection Features - IP40 Features	Lens Color	Blue
Voltage 5V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Lens Transparency	Diffused
Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Ratings	DC
Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features	Voltage	5V
Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Current	8mA
Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Panel Cutout Shape	Round
Millicandela Rating	Panel Cutout Dimensions	0.63" (16.00mm)
Wavelength - Peak Viewing Angle Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Lens Style/Size	Rectangle with Flat Top, 21.00mm x 15.10mm
Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Millicandela Rating	-
Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Wavelength - Peak	-
Ingress Protection IP40 Features -	Viewing Angle	-
Features -	Termination Style	Quick Connect - 0.110" (2.8mm)
	Ingress Protection	IP40
Report errors?	Features	-
		Report errors?

M16-JA-5D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M16-JA-5D Payment Methods



















M16-JA-5D Shipping Methods













If you have any question about M16-JA-5D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com