

M16-JY-24D Information

Heisener.com

Part Number M16-JY-24D

Manufacturer Omron Automation and Safety

Category Optoelectronics

Panel Indicators, Pilot Lights

PILOT LIGHT 24V LED RECT YELLOW **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M16-JY-24D Specifications

Manufacturer Part Number M16-JY-24D Manufacturer Omron Automation and Safety Category Optoelectronics Panel Indicators, Pilot Lights Package - Series M16 Type LED Lamp Color Yellow Lens Color Yellow Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features - Report errors?		
Category Optoelectronics Package - Series M16 Type LED Lamp Color Yellow Lens Color Yellow Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Manufacturer Part Number	M16-JY-24D
Package - Series M16 Type LED Lamp Color Yellow Lens Color Yellow Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak Viewing Angle - Cermination Style Termination Style Ingress Protection IP40 Features - Series M16.00mm ILED Series Protection IP40 Features - Cermination Series Indicators, Pilot Lights M16 Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Cermination Style Ingress Protection IP40 Features - Cermination Style Ingress Protection IP40 Features	Manufacturer	Omron Automation and Safety
Package - Series M16 Type LED Lamp Color Yellow Lens Color Yellow Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Category	Optoelectronics
Series M16 Type LED Lamp Color Yellow Lens Color Yellow Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorYellowLens ColorYellowLens TransparencyDiffusedRatingsAC/DCVoltage24VCurrent8mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRectangle with Flat Top, 21.00mm x 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP40Features-	Package	-
Lamp Color Lens Color Yellow Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Panel Cutout Dimensions I Quick Connect - 0.110" (2.8mm) I Peatures -	Series	M16
Lens Color Lens Transparency Diffused Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating	Туре	LED
Lens TransparencyDiffusedRatingsAC/DCVoltage24VCurrent8mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRectangle with Flat Top, 21.00mm x 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP40Features-	Lamp Color	Yellow
Ratings AC/DC Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features - 24V AC/DC AC/AC AC/DC AC/AC AC/DC AC/AC AC/DC AC/DC AC/AC AC/DC AC/AC AC/DC AC/AC AC/DC AC/AC AC/DC AC/DC AC/AC AC/AC AC/AC AC/AC AC/DC AC/AC AC/AC	Lens Color	Yellow
Voltage 24V Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Lens Transparency	Diffused
Current 8mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Ratings	AC/DC
Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Voltage	24V
Panel Cutout Dimensions O.63" (16.00mm) Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak Viewing Angle Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Current	8mA
Lens Style/Size Rectangle with Flat Top, 21.00mm x 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Panel Cutout Shape	Round
Millicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP40Features-	Panel Cutout Dimensions	0.63" (16.00mm)
Wavelength - Peak Viewing Angle Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Lens Style/Size	Rectangle with Flat Top, 21.00mm x 15.10mm
Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Millicandela Rating	-
Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP40 Features -	Wavelength - Peak	-
Ingress Protection IP40 Features -	Viewing Angle	-
Features -	Termination Style	Quick Connect - 0.110" (2.8mm)
	Ingress Protection	IP40
Report errors?	Features	-
		Report errors?

M16-JY-24D Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M16-JY-24D Payment Methods


































If you have any question about M16-JY-24D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com