

M165-TR-5 Information

Heisener.com

Part Number M165-TR-5

Manufacturer Omron Automation and Safety

Category Optoelectronics

Panel Indicators, Pilot Lights

Description PILOT LIGHT 5V INCAND ROUND RED

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M165-TR-5 Specifications

| Manufacturer Part Number M165-TR-5 Manufacturer Omron Automation and Safety Category Optoelectronics Panel Indicators, Pilot Lights Package - Series M16 Type Incandescent Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings AC/DC Voltage 6V Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | | |
|---|--------------------------|--------------------------------|
| CategoryOptoelectronicsPackage-SeriesM16TypeIncandescentLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsAC/DCVoltage6VCurrent60mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRound with Flat Top, 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP65FeaturesOil Resistant | Manufacturer Part Number | M165-TR-5 |
| Package Series M16 Type Incandescent Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings AC/DC Voltage 6V Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Old Termination Style Old Red Single Features Old Red Single Gentle Includes Indicators, Pilot Lights M16 Ingress Protection IP65 Features Oli Resistant | Manufacturer | Omron Automation and Safety |
| Package - Series M16 Type Incandescent Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings AC/DC Voltage 6V Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Category | Optoelectronics |
| SeriesM16TypeIncandescentLamp ColorRedLens ColorRedLens TransparencyDiffusedRatingsAC/DCVoltage6VCurrent60mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRound with Flat Top, 15.10mmMillicandela Rating-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP65FeaturesOil Resistant | | Panel Indicators, Pilot Lights |
| Type Incandescent Lamp Color Red Lens Color Red Lens Transparency Diffused Ratings AC/DC Voltage 6V Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Package | - |
| Lamp Color Lens Color Red Lens Transparency Diffused Ratings AC/DC Voltage 6V Current 60mA Panel Cutout Shape Panel Cutout Dimensions Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Peatures Red | Series | M16 |
| Lens ColorRedLens TransparencyDiffusedRatingsAC/DCVoltage6VCurrent60mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRound with Flat Top, 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP65FeaturesOil Resistant | Type | Incandescent |
| Lens TransparencyDiffusedRatingsAC/DCVoltage6VCurrent60mAPanel Cutout ShapeRoundPanel Cutout Dimensions0.63" (16.00mm)Lens Style/SizeRound with Flat Top, 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP65FeaturesOil Resistant | Lamp Color | Red |
| Ratings AC/DC Voltage 6V Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Lens Color | Red |
| Voltage 6V Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Lens Transparency | Diffused |
| Current 60mA Panel Cutout Shape Round Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Ratings | AC/DC |
| Panel Cutout Dimensions 0.63" (16.00mm) Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Voltage | 6V |
| Panel Cutout Dimensions Lens Style/Size Round with Flat Top, 15.10mm Millicandela Rating - Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features Oil Resistant | Current | 60mA |
| Lens Style/SizeRound with Flat Top, 15.10mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleQuick Connect - 0.110" (2.8mm)Ingress ProtectionIP65FeaturesOil Resistant | Panel Cutout Shape | Round |
| Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features - Oil Resistant - Oil Resistant | Panel Cutout Dimensions | 0.63" (16.00mm) |
| Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features - Quick Connect - 0.110" (2.8mm) IP65 Oil Resistant | Lens Style/Size | Round with Flat Top, 15.10mm |
| Viewing Angle Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Millicandela Rating | - |
| Termination Style Quick Connect - 0.110" (2.8mm) Ingress Protection IP65 Features Oil Resistant | Wavelength - Peak | - |
| Ingress Protection IP65 Features Oil Resistant | Viewing Angle | - |
| Features Oil Resistant | Termination Style | Quick Connect - 0.110" (2.8mm) |
| | Ingress Protection | IP65 |
| Report errors? | Features | Oil Resistant |
| | | Report errors? |

M165-TR-5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M165-TR-5 Payment Methods



















M165-TR-5 Shipping Methods













If you have any question about M165-TR-5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com