

M20-7851342 Information

Heisener.com

For Reference Only

Part Number M20-7851342
Manufacturer Harwin Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description 13+13 DIL BTM ENTRY SKT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M20-7851342 Specifications

| Manufacturer Part NumberM20-7851342ManufacturerHarwin Inc.CategoryConnectors, InterconnectsPackage-SeriesM20Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | | |
|--|-----------------------------------|---|
| CategoryConnectors, InterconnectsPackage-SeriesM20Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Manufacturer Part Number | M20-7851342 |
| Package-SeriesM20Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Manufacturer | Harwin Inc. |
| Package-SeriesM20Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Category | Connectors, Interconnects |
| SeriesM20Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Connector TypeReceptacle, Bottom or Top EntryContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Package | - |
| Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Series | M20 |
| StyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Connector Type | Receptacle, Bottom or Top Entry |
| Number of Positions 26 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black | Contact Type | Female Socket |
| Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black | Style | Board to Board or Cable |
| Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black | Number of Positions | 26 |
| Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Number of Positions Loaded | All |
| Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black | Pitch - Mating | 0.100" (2.54mm) |
| Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlack | Number of Rows | 2 |
| Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black | Row Spacing - Mating | 0.100" (2.54mm) |
| Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black | Mounting Type | Through Hole |
| Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black | Termination | Solder |
| Contact Finish Thickness - Mating Insulation Color Black | Fastening Type | Push-Pull |
| Insulation Color Black | Contact Finish - Mating | Gold |
| | Contact Finish Thickness - Mating | - |
| | Insulation Color | Black |
| Insulation Height 0.197" (5.00mm) | Insulation Height | 0.197" (5.00mm) |
| Contact Length - Post 0.118" (3.00mm) | Contact Length - Post | 0.118" (3.00mm) |
| Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ | Operating Temperature | -40°C ~ 105°C |
| Material Flammability Rating UL94 V-0 | Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin |
|------------------------|----------------|
| Mated Stacking Heights | - |
| Ingress Protection | - |
| Features | - |
| | Report errors? |

M20-7851342 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M20-7851342 Payment Methods



















M20-7851342 Shipping Methods













If you have any question about M20-7851342, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com