

### **M20-7881042 Information**

Heisener.com

For Reference Only

Part Number M20-7881042 Manufacturer Harwin Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** 10+10 DIL HORIZ SOCKET L/FREE

Package -

For the pricing/inventory/lead time, please contact

u

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **M20-7881042 Specifications**

Manufacturer Part Number         M20-7881042           Manufacturer         Harwin Inc.           Category         Connectors, Interconnects           Rectangular Connectors - Headers, Receptacles, Female Sockets           Package         -           Series         M20           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole, Right Angle           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.232" (5.90mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -40°C ~ 105°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         M20           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole, Right Angle           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.232" (5.90mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -40°C ~ 105°C	Manufacturer Part Number	M20-7881042
Package-SeriesM20Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Manufacturer	Harwin Inc.
Package         -           Series         M20           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole, Right Angle           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.232" (5.90mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -40°C ~ 105°C	Category	Connectors, Interconnects
Series         M20           Connector Type         Receptacle           Contact Type         Female Socket           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole, Right Angle           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.232" (5.90mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Series	M20
Style Board to Board or Cable  Number of Positions 20  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.232" (5.90mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -40°C ~ 105°C	Connector Type	Receptacle
Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole, Right Angle           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         -           Insulation Color         Black           Insulation Height         0.232" (5.90mm)           Contact Length - Post         0.118" (3.00mm)           Operating Temperature         -40°C ~ 105°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Style	Board to Board or Cable
Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.232" (5.90mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -40°C ~ 105°C	Number of Positions	20
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating  Mounting Type  Through Hole, Right Angle  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.232" (5.90mm)  Contact Length - Post  0.118" (3.00mm)  Operating Temperature	Pitch - Mating	0.100" (2.54mm)
Mounting Type Through Hole, Right Angle  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.232" (5.90mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -40°C ~ 105°C	Number of Rows	2
Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.232" (5.90mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating -  Insulation Color Black  Insulation Height 0.232" (5.90mm)  Contact Length - Post 0.118" (3.00mm)  Operating Temperature -40°C ~ 105°C	Mounting Type	Through Hole, Right Angle
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.232" (5.90mm)  Contact Length - Post  0.118" (3.00mm)  Operating Temperature  -40°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.232"$ (5.90mm)Contact Length - Post $0.118"$ (3.00mm)Operating Temperature $-40$ °C ~ $105$ °C	Contact Finish - Mating	Gold
Insulation Height $0.232" (5.90 \text{mm})$ Contact Length - Post $0.118" (3.00 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post $0.118'' (3.00 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.232" (5.90mm)
	Contact Length - Post	0.118" (3.00mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### **M20-7881042 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## M20-7881042 Payment Methods



















# M20-7881042 Shipping Methods













If you have any question about M20-7881042, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com