

M20-7881642 Information

Part Number M20-7881642
Manufacturer Harwin Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description 16+16 DIL HORIZ SOCKET L/FREE

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M20-7881642 Specifications

Manufacturer Part Number M20-7881642 Manufacturer Harwin Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series M20 Connector Type Receptacle Contact Type Female Socket Style Board or Cable Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C		
Category Connectors, Interconnects Package - Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	M20-7881642
Package-SeriesM20Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Manufacturer	Harwin Inc.
Package - Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects
Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions32Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Series	M20
Style Board to Board or Cable Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Connector Type	Receptacle
Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Style	Board to Board or Cable
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Number of Positions	32
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.232" (5.90mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Pitch - Mating	0.100" (2.54mm)
Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Mounting Type	Through Hole, Right Angle
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.232" (5.90mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.232"$ (5.90mm)Contact Length - Post $0.118"$ (3.00mm)Operating Temperature -40 °C ~ 105 °C	Contact Finish - Mating	Gold
Insulation Height $0.232" (5.90 \text{mm})$ Contact Length - Post $0.118" (3.00 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post $0.118" (3.00 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.232" (5.90mm)
	Contact Length - Post	0.118" (3.00mm)
	Operating Temperature	-40°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

M20-7881642 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M20-7881642 Payment Methods



















M20-7881642 Shipping Methods













If you have any question about M20-7881642, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com