

M20-7892046 Information

MANAPAPISEDER.COM

For Reference Only

Part Number M20-7892046 Manufacturer Harwin Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description 20-WAY SIL HORIZ SOCKET L/FREE

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M20-7892046 Specifications

Manufacturer Part Number M20-7892046 Manufacturer Harwin Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating 100µin (2.54µm) Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature 40°C ~ 105°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	M20-7892046
Package-SeriesM20Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100µin (2.54μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Manufacturer	Harwin Inc.
Package - Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μin (2.54μm) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects
Series M20 Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Series	M20
Style Board to Board or Cable Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Connector Type	Receptacle
Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole, Right Angle Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100µin (2.54µm) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Style	Board to Board or Cable
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Number of Positions	20
Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating 100μ in (2.54 μ m)Insulation ColorBlackInsulation Height 0.130 " (3.30mm)Contact Length - Post 0.118 " (3.00mm)Operating Temperature -40 °C ~ 105 °C	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100μin (2.54μm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)Operating Temperature-40°C ~ 105°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100 μ in (2.54 μ m) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating 100 μ in (2.54 μ m) Insulation Color Black Insulation Height 0.130" (3.30mm) Contact Length - Post 0.118" (3.00mm) Operating Temperature -40°C ~ 105°C	Mounting Type	Through Hole, Right Angle
Contact Finish - Mating Tin Contact Finish Thickness - Mating 100μ in (2.54 μ m) Insulation Color Black Insulation Height $0.130''$ (3.30mm) Contact Length - Post $0.118''$ (3.00mm) Operating Temperature -40° C ~ 105° C	Termination	Solder
Contact Finish Thickness - Mating 100μ in (2.54 μ m) Insulation Color Black Insulation Height 0.130 " (3.30mm) Contact Length - Post 0.118 " (3.00mm) Operating Temperature -40 °C ~ 105 °C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.130"$ ($3.30mm$)Contact Length - Post $0.118"$ ($3.00mm$)Operating Temperature -40 °C ~ 105 °C	Contact Finish - Mating	Tin
Insulation Height $0.130" (3.30mm)$ Contact Length - Post $0.118" (3.00mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	100μin (2.54μm)
Contact Length - Post $0.118'' (3.00 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.130" (3.30mm)
	Contact Length - Post	0.118" (3.00mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

M20-7892046 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M20-7892046 Payment Methods



















M20-7892046 Shipping Methods













If you have any question about M20-7892046, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com