

M20-7893046

est a Quote

M20-7893046 Information

	Part Number	M20-7893046
Citati server com	Manufacturer	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
	Description	30-WAY SIL HORIZ SOCKET L/FREE
	Package	-
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



M20-7893046 Specifications

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container></table-container></table-container></table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesM20Connector TypeReceptacleConnector TypeReceptacleContact TypeBoard to Board or CableNumber of Positions30Number of Positions LoadedIlPitch - Mating0.100° (2.54mm)Number of Rows1Number of Rows0.100° (2.54mm)Number of RowsSolderYourging - MatingSolderTerminationSolderForta Finish - MatingInContact Finish - MatingInContact Finish - MatingIniContact Finish Thickness - MatingIlInsulation ColorBlackInsulation Height0.130° (3.0mm)Contact Length - Post0.118° (3.00mm)	Manufacturer Part Number	M20-7893046	
NumberRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesM20Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypeUsh-PullContact Finish - Mating10jui (2.54µm)Contact Finish Finkenses - MatingIojui (2.54µm)Insulation ColorBlackInsulation Finish - Mating1.30° (3.30mm)Contact Fungh - Post0.130° (3.00mm)	Manufacturer	Harwin Inc.	
Package-SeriesM20Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeSolderTerminationSolderFastening TypeSolderContact Finish - Mating10u (2.54µm)Contact Finish - MatingSolderFastening TypeInfo (2.54µm)Contact Finish - MatingSolderInsulation ColorBlackInsulation Finish - Mating1.00µn (2.54µm)Insulation Finish - MatingSolderInsulation Finish - PostSolderInsulation Finish - PostSolderInsulation Finish - PostSolderInsulation Fin	Category	Connectors, Interconnects	
SeriesM20Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleFastening TypeOlderContact Finish - Mating0.010" (2.54µm)Contact Finish - MatingSolderFastening TypeUnsh-PullContact Finish - MatingDiale (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30µm)Contact Length - Post0.118" (3.00µm)		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBiackInsulation Finish Thickness - Mating100µin (2.54µm)Insulation Finish Thickness - Mating100µin (2.54µm)Insulation Height0.130" (3.30mm)Contact Finish Phost1.18" (3.00mm)	Package	-	
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeOlderFerminationSolderForstening TypePush-PullContact Finish - MatingInContact Finish - MatingIninInsulation ColorBlackInsulation Field0.130° (3.30mm)Contact Length - Post0.118° (3.00mm)	Series	M20	
StyleBoard to Board or CableStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Connector Type	Receptacle	
Yumber of Positions30Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Contact Type	Female Socket	
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.00mm)Contact Length - Post0.118" (3.00mm)	Style	Board to Board or Cable	
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting Type-TerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Number of Positions	30	
Number of Rows1Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Number of Positions Loaded	All	
Row Spacing - Mating-Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Pitch - Mating	0.100" (2.54mm)	
Mounting TypeThrough Hole, Right AngleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Number of Rows	1	
TerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Row Spacing - Mating	-	
Fastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Mounting Type	Through Hole, Right Angle	
Contact Finish - MatingTinContact Finish Thickness - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Termination	Solder	
Contact Finish Thickness - Mating100µin (2.54µm)Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Contact Finish - Mating	Tin	
Insulation Height0.130" (3.30mm)Contact Length - Post0.118" (3.00mm)	Contact Finish Thickness - Mating	100µin (2.54µm)	
Contact Length - Post 0.118" (3.00mm)	Insulation Color	Black	
• • • • • • • • • • • • • • • • • • •	Insulation Height	0.130" (3.30mm)	
	Contact Length - Post	0.118" (3.00mm)	
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Operating Temperature	-40°C ~ 105°C	
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
			Report errors?

M20-7893046 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about M20-7893046, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com