



M2012ES1W01 Information



For Reference Only

Part Number M2012ES1W01
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2012ES1W01 Specifications

Manufacturer Part Number M2012ES1W01 Manufacturer NKK Switches Category Switches Package - Series M Circuit SPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2012ES1W01
Toggle Switches Package - Series M Circuit SPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Flatted Actuator Length Illumination Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Fermination Style Panel Cutout Dimensions Sunday Sealed Terminals Toggle Switches	Manufacturer	NKK Switches
Package-SeriesMCircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesMCircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function Current Rating Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection - Features Epoxy Sealed Terminals	Series	M
Current Rating Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features 6A (AC), 4A (DC) 125V 125V 125V 126V 127V Patted Non-Illumination Non-Illuminated 11.40mm Non-Illuminated 11.40mm Non-Illuminated 11.40mm Non-Illuminated 11.40mm Non-Illuminated 11.40mm Non-Illuminated 11.40mm Circular - 6.50mm Dia 1/4-40 Ingress Protection - Features	Circuit	SPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Sushing Thread Ingress Protection Features Epoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	6A (AC), 4A (DC)
Actuator Type Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color	Voltage Rating - AC	125V
Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Flatted
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Length	11.40mm
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2012ES1W01 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2012ES1W01 Payment Methods



















M2012ES1W01 Shipping Methods













If you have any question about M2012ES1W01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com