



M2012S2A1G32 Information

Heisener.com

Part Number M2012S2A1G32
Manufacturer NKK Switches
Category Switches

Switches Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 28V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2012S2A1G32 Specifications

Manufacturer Part Number M2012S2A1G32 Manufacturer NKK Switches Category Switches Package - Series M Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2012S2A1G32
Package - Series M Circuit SPDT Switch Function On-On Current Rating	Manufacturer	NKK Switches
Package - Series M Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
SeriesMCircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Series	M
Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	28V
Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	6.86mm
Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia 1/4-40 Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals	Mounting Type	Panel Mount, Right Angle
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2012S2A1G32 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2012S2A1G32 Payment Methods



















M2012S2A1G32 Shipping Methods













If you have any question about M2012S2A1G32, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com