



## M2012S3D3G03 Information



For Reference Only

Part Number M2012S3D3G03 Manufacturer NKK Switches Category Switches

Toggle Switches

**Description** SWITCH TOGGLE SPDT 0.4VA 28V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2012S3D3G03	<b>Specifications</b>
--------------	-----------------------

Manufacturer         NKK Switches           Category         Switches           Toggle Switches         Toggle Switches           Package         -           Series         M           Circuit         SPDT           Switch Function         On-On           Current Rating         0.4VA (AC/DC)           Voltage Rating - AC         28V           Voltage Rating - DC         28V           Actuator Type         Standard Round           Actuator Length         6.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         PC Pin           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         IP67 - Dust Tight, Waterproof	*	
Category         Switches           Package         -           Series         M           Circuit         SPDT           Switch Function         On-On           Current Rating         0.4VA (AC/DC)           Voltage Rating - AC         28V           Voltage Rating - DC         28V           Actuator Type         Standard Round           Actuator Length         6.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         PC Pin           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         IP67 - Dust Tight, Waterproof           Features         Epoxy Sealed Terminals	Manufacturer Part Number	M2012S3D3G03
Toggle Switches	Manufacturer	NKK Switches
Package - Series M M  Circuit SPDT  Switch Function On-On  Current Rating 0.4VA (AC/DC)  Voltage Rating - AC 28V  Voltage Rating - DC 28V  Actuator Type Standard Round  Actuator Length 6.50mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style PC Pin  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection IP67 - Dust Tight, Waterproof  Features Epoxy Sealed Terminals	Category	Switches
Series         M           Circuit         SPDT           Switch Function         On-On           Current Rating         0.4VA (AC/DC)           Voltage Rating - AC         28V           Voltage Rating - DC         28V           Actuator Type         Standard Round           Actuator Length         6.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         PC Pin           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         IP67 - Dust Tight, Waterproof           Features         Epoxy Sealed Terminals		Toggle Switches
Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Package	-
Switch Function Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Ingress Protection IP67 - Dust Tight, Waterproof Features  On-On On-On On-On On-On On-On On-On On-On On-On On-On On On-On On On-On On On-On On O	Series	M
Current Rating 0.4VA (AC/DC)  Voltage Rating - AC 28V  Voltage Rating - DC 28V  Actuator Type Standard Round  Actuator Length 6.50mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style PC Pin  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection IP67 - Dust Tight, Waterproof  Features Epoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC  Voltage Rating - DC  28V  Actuator Type  Standard Round  Actuator Length  6.50mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  PC Pin  Panel Cutout Dimensions  Bushing Thread  Ingress Protection  Features  28V  28V  28V  28V  28V  28V  28V  28	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 6.50mm  Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal)  Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Voltage Rating - AC	28V
Actuator Length  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Bushing Thread  Ingress Protection  Features  6.50mm  Pond  Pond  Circular - 6.50mm  Dia  1/4-40  Ingress Protection  IP67 - Dust Tight, Waterproof  Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style PC Pin  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection IP67 - Dust Tight, Waterproof  Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style PC Pin  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Actuator Length	6.50mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  PC Pin  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection IP67 - Dust Tight, Waterproof  Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Panel Mount  Termination Style PC Pin  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection IP67 - Dust Tight, Waterproof  Features Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Circular - 6.50mm Dia  1/4-40  Ingress Protection  IP67 - Dust Tight, Waterproof  Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection IP67 - Dust Tight, Waterproof Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection IP67 - Dust Tight, Waterproof Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	IP67 - Dust Tight, Waterproof
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### M2012S3D3G03 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## M2012S3D3G03 Payment Methods



















## M2012S3D3G03 Shipping Methods













If you have any question about M2012S3D3G03, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com