

M2013B2B1W01-VE

M2013B2B1W01-VE Information

Heisener.com

Part Number M2013B2B1W01-VE

Manufacturer NKK Switches

Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2013B2B1W01-VE Specifications

| Manufacturer Part Number M2013B2B1W01-VE Manufacturer NKK Switches Category Switches Package - Series M Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | | |
|--|--------------------------------|-------------------------|
| Category Switches Package - Series M Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125 V Voltage Rating - DC 30 V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Manufacturer Part Number | M2013B2B1W01-VE |
| Toggle Switches Package - Series M Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Sundard Sundar | Manufacturer | NKK Switches |
| Package - Series M Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Category | Switches |
| Series M Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | | Toggle Switches |
| Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Package | - |
| Switch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard Round with CapActuator Length18.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesYellow Cap | Series | M |
| Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Circuit | SPDT |
| Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Switch Function | On-Off-On |
| Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features Yellow Cap | Current Rating | 6A (AC), 3A (DC) |
| Actuator Type Standard Round with Cap Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Voltage Rating - AC | 125V |
| Actuator Length 18.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Voltage Rating - DC | 30V |
| Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Actuator Type | Standard Round with Cap |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesYellow Cap | Actuator Length | 18.50mm |
| Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesYellow Cap | Illumination | Non-Illuminated |
| Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesYellow Cap | Illumination Type, Color | - |
| Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features Yellow Cap | Mounting Type | Panel Mount |
| Bushing Thread M12 x 1 Ingress Protection - Features Yellow Cap | Termination Style | Solder Lug |
| Ingress Protection - Features Yellow Cap | Panel Cutout Dimensions | Circular - 12.50mm Dia |
| Features Yellow Cap | Bushing Thread | M12 x 1 |
| - | Ingress Protection | - |
| Report errors? | Features | Yellow Cap |
| | | Report errors? |

M2013B2B1W01-VE Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2013B2B1W01-VE Payment Methods





















M2013B2B1W01-VE Shipping Methods













If you have any question about M2013B2B1W01-VE, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com