



### M2013B2B1W01 Information



For Reference Only

Part Number M2013B2B1W01
Manufacturer NKK Switches
Category Switches

**Toggle Switches** 

**Description** SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## M2013B2B1W01 Specifications

Manufacturer Part Number         M2013B2B1W01           Manufacturer         NKK Switches           Category         Switches           Package         -           Series         M           Circuit         SPDT           Switch Function         On-Off-On           Current Rating         6A (AC), 3A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Vyleage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2013B2B1W01
Package - Series M M Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Monuting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	NKK Switches
Package         -           Series         M           Circuit         SPDT           Switch Function         On-Off-On           Current Rating         6A (AC), 3A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         Epoxy Sealed Terminals	Category	Switches
Series         M           Circuit         SPDT           Switch Function         On-Off-On           Current Rating         6A (AC), 3A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         Epoxy Sealed Terminals		Toggle Switches
Circuit         SPDT           Switch Function         On-Off-On           Current Rating         6A (AC), 3A (DC)           Voltage Rating - AC         125 V           Voltage Rating - DC         30 V           Actuator Type         Standard Round           Actuator Length         17.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 12.50mm Dia           Bushing Thread         M12 x 1           Ingress Protection         -           Features         Epoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	M
Current Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length17.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 17.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC), 3A (DC)
Actuator Type Standard Round  Actuator Length 17.50mm  Illumination Non-Illuminated  Illumination Type, Color Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection -  Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length 17.50mm  Illumination Non-Illuminated  Illumination Type, Color -  Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection -  Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 12.50mm Dia Bushing Thread M12 x 1 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	17.50mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 12.50mm DiaBushing ThreadM12 x 1Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug  Panel Cutout Dimensions Circular - 12.50mm Dia  Bushing Thread M12 x 1  Ingress Protection -  Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Circular - 12.50mm Dia  Bushing Thread  M12 x 1  Ingress Protection  Features  Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread M12 x 1 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 12.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	M12 x 1
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### M2013B2B1W01 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## M2013B2B1W01 Payment Methods



















### **M2013B2B1W01 Shipping Methods**













If you have any question about M2013B2B1W01, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com