



M2013S2A2G30 Information



For Reference Only

Part Number M2013S2A2G30 Manufacturer NKK Switches Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 28V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2013S2A2G30 Specifications

Manufacturer Part Number M2013S2A2G30 Manufacturer NKK Switches Category Switches Package - Series M Circuit SPDT Switch Function On-Off-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2013S2A2G30
Package - Series M M Circuit SPDT Switch Function On-Off-On Current Rating O.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Monunding Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Sundard Round - Unthreaded Ingress Protection - Epoxy Sealed Terminals	Manufacturer	NKK Switches
Package-SeriesMCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesMCircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-Off-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Series	M
Current Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	28V
Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	28V
Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	6.86mm
Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2013S2A2G30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2013S2A2G30 Payment Methods



















M2013S2A2G30 Shipping Methods













If you have any question about M2013S2A2G30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com