



M2015SA2A13 Information



For Reference Only

Part NumberM2015SA2A13ManufacturerNKK SwitchesCategorySwitches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2015SA2A13 Specifications

Manufacturer Part Number M2015SA2A13 Manufacturer NKK Switches Category Switches Package - Series M Circuit SPDT Switch Function On-Mom Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitSPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2015SA2A13
Package - Series M M Circuit SPDT Switch Function On-Mom Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 12.27mm Illumination Uppe, Color 112.7mm Illumination Type, Color - Illumination Type, Color 112.7mm Illumination Voltage (Nominal) - Moneting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Epoxy Sealed Terminals	Manufacturer	NKK Switches
Package-SeriesMCircuitSPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesMCircuitSPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function On-Mom Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Through Hole Termination Style PC Pin Panel Cutout Dimensions - Sushing Thread Unthreaded Ingress Protection - Epoxy Sealed Terminals	Series	M
Current Rating Current Rating Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 12.27mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 6A (AC), 3A (DC) 125V 125V 126V Standard Round 12.27mm Non-Illuminated 12.27mm Non-Illuminated 12.27mm Through Hole - Unthreaded Unthreaded Fermination Style Features	Circuit	SPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Mom
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	6A (AC), 3A (DC)
Actuator Type Standard Round Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Through Hole Termination Style PC Pin Panel Cutout Dimensions - Panel Cutout Dimensions - Unthreaded Ingress Protection - Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	12.27mm
Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole
Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2015SA2A13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2015SA2A13 Payment Methods



















M2015SA2A13 Shipping Methods













If you have any question about M2015SA2A13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com