

# M2018SA1G01

### M2018SA1G01 Information

Heisener.com Gittar service starts they	 M2018SA1G01 NKK Switches Switches Toggle Switches SWITCH TOGGLE SPDT 0.4VA 28V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## M2018SA1G01 Specifications

Manufacturer Part Number M2018SA1G01   Manufacturer Part Number NKK Switches   Category Switches   Category Toggle Switches   Package -   Series M   Circuit SPDT   Switch Function Mom-Off-Mom   Current Rating 0.4VA (AC/DC)   Voltage Rating - AC 28V   Voltage Rating - DC Standard Round   Actuator Length 12.27mm   Illumination Non-Illuminated   Illumination Type, Color -   Illumination Voltage (Nominal) -   Termination Style Solder Lug   Patel Cutout Dimensions Gicrular - 6.50mm Dia   Bushing Thread 1.440   Ingress Protection -		
Switches       Toggle Switches       Package     -       Series     M       Circuit     SPDT       Switch Function     MomOff-Mom       Current Rating     0.4VA (AC/DC)       Voltage Rating - AC     28V       Voltage Rating - DC     28V       Actuator Type     28V       Illumination     12.27mm       Illumination Type, Color     -       Illumination Type, Color     -	Manufacturer Part Number	M2018SA1G01
Togle SwitchesPackage-SeriesMCircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.27nmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	NKK Switches
Package.SeriesMCircuitSPDTSwitch FunctionMon-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - ACS8VXoltage Rating - DCSaknadard RoundActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Mouting TypeSolder LugInduning TypeSolder LugInduning StyleSolder LugInduning StyleSolder LugInduning StyleSolder LugInder StyleSolder StyleInder StyleSolder StyleInder StyleSolder StyleInder StyleSolder Style </td <td>Category</td> <td>Switches</td>	Category	Switches
SeriesMCircuitSPDTSwitch FunctionMon-Off-MornCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fermination StyleSuder LugPanel Cutout DimensionsSolder LugBushing Thread1/440Ingress Protection-FeaturesEpoxy Sealed TerminatesFeaturesEpoxy Sealed Terminates		Toggle Switches
CircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length1.2.7mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminalis	Package	-
Switch FunctionMom-Off-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DCStandard RoundActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeSolder LugTermination StyleSolder LugPanel Cutour DimensionsCircular - 6.50mm DiaBushing Thread1/4-40FeaturesEpoxy Sealed Terminals	Series	М
Current Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStoler LugPanel MountStoler LugIndex StyleStoler LugPanel Style-Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Staled Terminales	Circuit	SPDT
Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandar RoundActuator Length12.27nmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	Mom-Off-Mom
Voltage Rating - DC28VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	0.4VA (AC/DC)
Actuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	28V
Actuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	28V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Length	12.27mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection -   Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### M2018SA1G01 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## M2018SA1G01 Payment Methods



### M2018SA1G01 Shipping Methods



If you have any question about M2018SA1G01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com