

# M2018SS1W30

### M2018SS1W30 Information

Heisener.com	 M2018SS1W30 NKK Switches Switches Toggle Switches SWITCH TOGGLE SPDT 6A 125V - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## M2018SS1W30 Specifications

Manufacturer Part Number M2018SS1W30   Manufacturer NKK Switches   Category Switches   Toggle Switches Toggle Switches   Package -   Series M   Circuit SPDT   Switch Function Mom-Off-Mom   Current Rating 6A (AC), 3A (DC)   Voltage Rating - AC 30V   Voltage Rating - DC 30V   Actuator Type Standard Round   Actuator Length 10.50mm   Illumination Non-Illuminated   Illumination Type, Color -   Termination Style PC Pin   Panel Cutout Dimensions Circular - 6.50mm Dia   Bushing Thread 1/4-40   Ingress Protection -   Features Epoxy Sealed Terminals	•	
CategorySwitchesPackage-SeriesMCircuitSPDTSwitch FunctionMom-Off-MomCurrent RatingA(AC), 3A (DC)Voltage Rating - ACSivVoltage Rating - DCSivActuator TypeSandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage Nominality-Ilumination SylePC PinTermination SyleCircular - 6.50mm DiaInder Loutor Lingth-Ilumination Syle-Shang Thread-Shang Thread <td>Manufacturer Part Number</td> <td>M2018SS1W30</td>	Manufacturer Part Number	M2018SS1W30
Toggle SwitchesPackage-SeriesMCircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC30VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCrcular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer	NKK Switches
Package-SeriesMCircuitSPDTSwitch FunctionMom-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator LengthNon-IlluminatedIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Mouting TypePanel Mount, Right AngleTermination StyleCircular - 6.50mm DialPanel Cutout DimensionsCircular - 6.50mm DialBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesMCircuitSPDTSwitch FunctionMom-Off-MomCurrent RatingGA (AC), 3A (DC)Voltage Rating - AC30VVoltage Rating - DCSandard RoundActuator TypeStandard RoundActuator Length1.050nmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Voltage (Nominal)-Premination StylePen Mount, Right AnglePanel Cutout DimensionsCircular - 6.50nm DialBushing Thread1/4-40Ingress Protection-FeaturesEposySeat Carculan StyleFeaturesEposySeat Carculan Style		Toggle Switches
CircuitSPDTSwitch FunctionMom-Off-MomCurrent RatingMom-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Fremination StylePanel Mount, Right AnglePanel Cutout DimensionsCircular 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionMom-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpsy Sealed Terminals	Series	М
Current Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StyleCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEposySeated Engradies	Switch Function	Mom-Off-Mom
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Current Rating	6A (AC), 3A (DC)
Actuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Voltage Rating - DC	30V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Termination	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	10.50mm
Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Mounting Type	Panel Mount, Right Angle
Bushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection-FeaturesEpoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### M2018SS1W30 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### M2018SS1W30 Payment Methods



## M2018SS1W30 Shipping Methods



If you have any question about M2018SS1W30, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com