



### M2021SS1W01-BA Information



For Reference Only

Part Number M2021SS1W01-BA
Manufacturer NKK Switches
Category Switches

Toggle Switches

**Description** SWITCH TOGGLE DPST 6A 125V

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **M2021SS1W01-BA Specifications**

Manufacturer Part Number         M2021SSIW01-BA           Manufacturer         NKK Switches           Category         Switches           Package         -           Series         M           Circuit         DPST           Switch Function         On-Off           Current Rating         6A (AC), 4A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Standard Round with Cap           Actuator Length         13.50mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         -		
CategorySwitchesPackage-SeriesMCircuitDPSTSwitch FunctionOn-OffCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Manufacturer Part Number	M2021SS1W01-BA
Package - Series M M Circuit DPST Switch Function On-Off Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Circular - 6.50mm Dia	Manufacturer	NKK Switches
Package-SeriesMCircuitDPSTSwitch FunctionOn-OffCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Category	Switches
SeriesMCircuitDPSTSwitch FunctionOn-OffCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-		Toggle Switches
CircuitDPSTSwitch FunctionOn-OffCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Package	-
Switch Function Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Illumination Voltage (Nominal) Type, Color Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection On-Off 6A (AC), 4A (DC) Actual (DC) Standard Round Non-Illumination Style Standard Round with Cap Actuator Length 13.50mm Non-Illuminated 13.50mm Panel Mount Standard Round with Cap Standard Round Round With Cap Standard Round Rou	Series	M
Current Rating  Current Rating - AC  Voltage Rating - AC  125V  Voltage Rating - DC  30V  Actuator Type  Standard Round with Cap  13.50mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Circular - 6.50mm Dia  Bushing Thread  Ingress Protection  6A (AC), 4A (DC)  125V  125V  1050  1050  Standard Round with Cap  13.50mm  Non-Illuminated  13.50mm  Panel Mount  Solder Lug  Panel Mount  1-4-40  1/4-40	Circuit	DPST
Voltage Rating - AC  Voltage Rating - DC  30V  Actuator Type  Standard Round with Cap  Actuator Length  13.50mm  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Panel Cutout Dimensions  Circular - 6.50mm Dia  Bushing Thread  Ingress Protection  125V  30V  30V  30V  30V  30V  30V  Actuator Lap  Actuator Lap  Annual Round with Cap  13.50mm  Non-Illuminated  Panel Mount  Circular - 6.50mm Dia  1/4-40  Ingress Protection  -	Switch Function	On-Off
Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection -  30V 30V 30V 30V 30V 30V 30V 30V 30V 30	Current Rating	6A (AC), 4A (DC)
Actuator Type Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color	Voltage Rating - AC	125V
Actuator Length 13.50mm  Illumination Non-Illuminated	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection	Actuator Type	Standard Round with Cap
Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection -	Actuator Length	13.50mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection -	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Illumination Type, Color	-
Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection -	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection -	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	Circular - 6.50mm Dia
	Bushing Thread	1/4-40
T	Ingress Protection	-
Features Black Cap	Features	Black Cap
Report errors?		Report errors?

#### M2021SS1W01-BA Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **M2021SS1W01-BA Payment Methods**



















### M2021SS1W01-BA Shipping Methods













If you have any question about M2021SS1W01-BA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com