



M2022E2S1W30 Information

Heisener.com

Part Number M2022E2S1W30
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2022E2S1W30 Specifications

Manufacturer Part Number M2022E2S1W30 Manufacturer NKK Switches Category Switches Package - Series M Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
Category Switches Package - Series M Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125 V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer Part Number	M2022E2S1W30
Package - Series M Circuit DPDT Switch Function On-On Current Rating AC Voltage Rating - AC Voltage Rating - DC Actuator Type Flatted Actuator Length Somm Illumination Type, Color Illumination Type, Color Illumination Voltage (Nominal) Fermination Style Penel Mount, Right Angle Permination Style Penel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Manufacturer	NKK Switches
Package - Series M Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
SeriesMCircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length6.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length6.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color	Series	M
Current Rating Current Rating Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features 6A (AC), 4A (DC) 125V 125V 125V 125V 1050 1060 1070 1080 1090	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length6.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Flatted Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC), 4A (DC)
Actuator Type Flatted Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length 6.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Clumination Voltage (Nominal) - Mounting Type Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Flatted
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Actuator Length	6.50mm
Illumination Voltage (Nominal) Mounting Type Panel Mount, Right Angle PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel Mount, Right AngleTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia 1/4-40 Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals	Mounting Type	Panel Mount, Right Angle
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2022E2S1W30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2022E2S1W30 Payment Methods



















M2022E2S1W30 Shipping Methods













If you have any question about M2022E2S1W30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com