

M2022S2A2W30 Information



For Reference Only

Part Number M2022S2A2W30 Manufacturer NKK Switches Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2022S2A2W30 Specifications

Manufacturer Part Number M2022S2A2W30 Manufacturer NKK Switches Category Switches Package - Series M Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125 VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2022S2A2W30
Toggle Switches Package - Series M Circuit DPDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Toggle Switches Toggle Switches Toggle Switches - How a suit of the suit o	Manufacturer	NKK Switches
Package-SeriesMCircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesMCircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard RoundActuator Length6.86mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function Current Rating Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 6.86mm Illumination Illumination Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Series	M
Current Rating Current Rating Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal)	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V 30V Standard Round 6.86mm Non-Illumination Fanda Ponel Unthreaded 10threaded	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features By Standard Round Standard Round Features Standard Round Ingress Protection - Epoxy Sealed Terminals	Current Rating	6A (AC), 4A (DC)
Actuator Type Standard Round Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length 6.86mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	6.86mm
Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection Features Unthreaded Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2022S2A2W30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2022S2A2W30 Payment Methods



















M2022S2A2W30 Shipping Methods













If you have any question about M2022S2A2W30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com