



M2023SS1W01-BF Information

Heisener.com

For Reference Only

Part Number M2023SS1W01-BF

Manufacturer NKK Switches

Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2023SS1W01-BF Specifications

Manufacturer Part Number M2023SS1W01-BF Manufacturer NKK Switches Category Switches Package - Series M Circuit DPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap		
Category Switches Toggle Switches Package - Series M Circuit DPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125 V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Manufacturer Part Number	M2023SS1W01-BF
Toggle Switches Package - Series M Circuit DPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Sundard Sundard Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Ingress Protection Features Green Cap	Manufacturer	NKK Switches
Package - Series M Circuit DPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Category	Switches
SeriesMCircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap	Package	-
Switch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap	Series	M
Current Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard Round with CapActuator Length13.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V 30V 30V 30V 30V Standard Round with Cap Actuator Lap Standard Round with Cap And Actuator Lap Standard Round with Cap 30V Standard Round with Cap 30V Standard Round with Cap Actuator Lap Standard Round with Cap Actuator Lap Solden 13.50mm Non-Illuminated - Circular - 6.50mm Dia 1/4-40 Ingress Protection Green Cap	Switch Function	On-Off-On
Voltage Rating - DC Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Green Cap	Current Rating	6A (AC), 3A (DC)
Actuator Type Standard Round with Cap Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Voltage Rating - AC	125V
Actuator Length 13.50mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Actuator Type	Standard Round with Cap
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap	Actuator Length	13.50mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesGreen Cap	Illumination Type, Color	-
Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection Features Green Cap	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Green Cap	Termination Style	Solder Lug
Ingress Protection - Features Green Cap	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Green Cap	Bushing Thread	1/4-40
-	Ingress Protection	-
Report errors?	Features	Green Cap
		Report errors?

M2023SS1W01-BF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2023SS1W01-BF Payment Methods





















M2023SS1W01-BF Shipping Methods













If you have any question about M2023SS1W01-BF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com