



M2029E3A1W13 Information

Heisener.com

Part NumberM2029E3A1W13ManufacturerNKK SwitchesCategorySwitches

Switches
Toggle Switches

Description SWITCH TOGGLE DPDT 6A 125V

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2029E3A1W13 Specifications

Manufacturer Part Number M2029E3A1W13 Manufacturer NKK Switches Category Switches Package - Series M Circuit DPDT Switch Function On-Off-Mom Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length - Illumination Non-Illuminated Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2029E3A1W13
Package - Series M M Circuit DPDT Switch Function On-Off-Mom Current Rating AC 125V Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length - Sillumination Non-Illuminated Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features DPDT	Manufacturer	NKK Switches
Package-SeriesMCircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesMCircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitDPDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeFlattedActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function On-Off-Mom Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Series	M
Current Rating Current Rating Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features 6A (AC), 3A (DC) 125V 125V	Circuit	DPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-Off-Mom
Voltage Rating - DC Actuator Type Flatted Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC), 3A (DC)
Actuator Type Flatted Actuator Length - Comment	Voltage Rating - AC	125V
Actuator Length - Illumination Non-Illuminated Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Clircular - General Mounting Type Panel Mount PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Actuator Type	Flatted
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Length	-
Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StylePC PinPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2029E3A1W13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2029E3A1W13 Payment Methods



















M2029E3A1W13 Shipping Methods













If you have any question about M2029E3A1W13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com