



### M2032ES1A01/U Information

Heisener.com

Part Number M2032ES1A01/U Manufacturer NKK Switches

Category Switches
Toggle Switches

**Description** SWITCH TOGGLE 3PDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# M2032ES1A01/U Specifications

Manufacturer Part Number         M2032ES1A01/U           Manufacturer         NKK Switches           Category         Switches           Package         -           Series         M           Circuit         3PDT           Switch Function         On-On           Current Rating         6A (AC), 4A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Flatted           Actuator Length         11.40mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuit3PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2032ES1A01/U
Package - Series M M Circuit 3PDT Switch Function On-On Current Rating AC 125V Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Flatted Actuator Length 11.40mm Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Monuting Type Panel Mount Termination Style Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Manufacturer	NKK Switches
Package         -           Series         M           Circuit         3PDT           Switch Function         On-On           Current Rating         6A (AC), 4A (DC)           Voltage Rating - AC         125V           Voltage Rating - DC         30V           Actuator Type         Flatted           Actuator Length         11.40mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals	Category	Switches
SeriesMCircuit3PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
Circuit         3PDT           Switch Function         On-On           Current Rating         6A (AC), 4A (DC)           Voltage Rating - AC         125 V           Voltage Rating - DC         30 V           Actuator Type         Flatted           Actuator Length         11.40mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Solder Lug           Panel Cutout Dimensions         Circular - 6.50mm Dia           Bushing Thread         1/4-40           Ingress Protection         -           Features         Epoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Series	M
Current Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Circuit	3PDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeFlattedActuator Length11.40mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Flatted Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features  Solv Flatted Solv Flatted Instruct Solor Flatted Instruct	Current Rating	6A (AC), 4A (DC)
Actuator Type Actuator Length 11.40mm Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal)	Voltage Rating - AC	125V
Actuator Length 11.40mm  Illumination Non-Illuminated  Illumination Type, Color - Illumination Voltage (Nominal) -  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection -  Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Solder Lug Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Flatted
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	11.40mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Solder Lug  Panel Cutout Dimensions Circular - 6.50mm Dia  Bushing Thread 1/4-40  Ingress Protection -  Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Circular - 6.50mm Dia  Bushing Thread  1/4-40  Ingress Protection  Features  Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	Solder Lug
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

#### M2032ES1A01/U Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## M2032ES1A01/U Payment Methods



















## M2032ES1A01/U Shipping Methods













If you have any question about M2032ES1A01/U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com