



M2032KS1W08 Information

Heisener.com

For Reference Only

Part Number M2032KS1W08 Manufacturer NKK Switches Category Switches

Toggle Switches

Description SWITCH TOGGLE 3PDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2032KS1W08 Specifications

Manufacturer Part Number M2032KS1W08 Manufacturer NKK Switches Category Switches Package - Series M Circuit 3PDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		
CategorySwitchesPackage-SeriesMCircuit3PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2032KS1W08
Toggle Switches Package - Series M Circuit 3PDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Lever for Cap Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Ingress Protection - Features Epoxy Sealed Terminals	Manufacturer	NKK Switches
Package - Series M M Circuit 3PDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Lever for Cap Actuator Length - Non-Illuminated Illumination Type, Color - Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Category	Switches
Series M Circuit 3PDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals		Toggle Switches
Circuit3PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeLever for CapActuator Length-IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch Function Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features On-On 6A (AC), 4A (DC) 6A (AC),	Series	M
Current Rating Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features 6A (AC), 4A (DC) 125V A (DC) 125V 125V 125V 30V Lever for Cap - Lever for Cap - Lever for Cap Actuator Length - University of the properties of th	Circuit	3PDT
Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Lever for Cap Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V 30V 10Ever for Cap Actuator Length - Panel Mount Non-Illuminated Won-Illuminated Wine Wrap Panel Mount Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Lever for Cap Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Bushing Thread Ingress Protection Features 30V Lever for Cap Lever for Cap Lever for Cap Non-Illumination Non-Illuminated Non-Illuminated Vine Una Lever for Cap Non-Illuminated Illuminated Illuminated 1	Current Rating	6A (AC), 4A (DC)
Actuator Type Actuator Length - Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - AC	125V
Actuator Length - Illumination Non-Illuminated Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Epoxy Sealed Terminals	Voltage Rating - DC	30V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Type	Lever for Cap
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	-
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals	Illumination	Non-Illuminated
Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals	Illumination Type, Color	-
Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions Bushing Thread Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals	Mounting Type	Panel Mount
Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals	Termination Style	Wire Wrap
Ingress Protection - Features Epoxy Sealed Terminals	Panel Cutout Dimensions	Circular - 6.50mm Dia
Features Epoxy Sealed Terminals	Bushing Thread	1/4-40
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
		Report errors?

M2032KS1W08 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2032KS1W08 Payment Methods



















M2032KS1W08 Shipping Methods













If you have any question about M2032KS1W08, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com