

# M2039SS1W01

### M2039SS1W01 Information



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## M2039SS1W01 Specifications

Manufacturer Part NumberM2039SS1W01Manufacturer AutometerNKK SwitchesCategorySwitchesPackage-SeriesMCircuit3PDTSwitch FunctionOn-Off-MomCurren Rating6A (AC), 3A (DC)Voltage Rating - AC3VVVoltage Rating - DC30VActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination TypeSolder LugMounting TypeSolder LugMounting TypeSolder LugFerniano StyleSolder LugFautores Protection-FautometerSolder LugFautometerSolder Solder FautometerFautometerSolder Solder Sold	•	
CategorySwitchesPackage-SeriesMCircuit3PDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC30VVoltage Rating - DC30VActuator TypeStandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination TypeSolder LugMouting TypeSolder LugTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaInshing Thread1/4-40Ingress Protection-Starter Street1/4-40	Manufacturer Part Number	M2039SS1W01
Togle SwitchesPackage-SeriesMCircuit3PDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundIluminationNon-IlluminatedIlumination Type, Color-Ilumination TypeSolder LugMounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaIngress Protection-Ingress Protection-	Manufacturer	NKK Switches
Package-SeriesMCircuit3PDTSwich FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC30VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIluminationNon-IlluminatedIlumination Type, Color-Ilumination Type, Color-Anonty TypePael MountIndining TypeSider LugIndining TypeSider LugInding TypeSider LugStandard StafeSider LugInding TypeSider LugStafe TypeSider Sider Si	Category	Switches
SeriesMCircuit3PDTSwitch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StyleSolder LugPanel MountSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/440Ingress Protection-		Toggle Switches
Circuit3PDTSwitch FunctionOn-Off-MornCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Illumination Voltage (Nominal)Stolder LugMounting TypeSolder LugPanel Cutout DimensionsSolder LugBushing Thread1/4-40Ingress Protection-	Package	-
Switch FunctionOn-Off-MomCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Voltage (Nominal)-Illumination Voltage (Nominal)Solder LugActuator SyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Series	М
Current Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeStale LugPanel MountStoler LugPanel MountCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Circuit	3PDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandar RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Switch Function	On-Off-Mom
Voltage Rating - DC30VActuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Current Rating	6A (AC), 3A (DC)
Actuator TypeStandard RoundActuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Voltage Rating - AC	125V
Actuator Length10.50mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Voltage Rating - DC	30V
IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Actuator Type	Standard Round
Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Actuator Length	10.50mm
Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Illumination	Non-Illuminated
Mounting TypePanel MountTermination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Illumination Type, Color	-
Termination StyleSolder LugPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Illumination Voltage (Nominal)	-
Panel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-	Mounting Type	Panel Mount
Bushing Thread1/4-40Ingress Protection-	Termination Style	Solder Lug
Ingress Protection -	Panel Cutout Dimensions	Circular - 6.50mm Dia
	Bushing Thread	1/4-40
Features Epoxy Sealed Terminals	Ingress Protection	-
	Features	Epoxy Sealed Terminals
Report errors?		Report errors?

#### M2039SS1W01 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## M2039SS1W01 Payment Methods



## M2039SS1W01 Shipping Methods



If you have any question about M2039SS1W01, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com