



M2042SA1W08 Information

Heisener.com

For Reference Only

Part Number M2042SA1W08 Manufacturer NKK Switches Category Switches

Switches Toggle Switches

Description SWITCH TOGGLE 4PDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2042SA1W08 Specifications

| Manufacturer Part Number M20428A1W08 Manufacturer NKK Switches Category Switches Package - Series M Circuit 4PDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | | |
|--|--------------------------------|------------------------|
| CategorySwitchesPackage-SeriesMCircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Manufacturer Part Number | M2042SA1W08 |
| Toggle Switches Package - Series M Circuit 4PDT Switch Function On-On Current Rating 6A (AC), 4A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Type Standard Round Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Fermination Style Panel Cutout Dimensions University of the suit of | Manufacturer | NKK Switches |
| Package-SeriesMCircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Termination StylePanel MountPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Category | Switches |
| SeriesMCircuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | | Toggle Switches |
| Circuit4PDTSwitch FunctionOn-OnCurrent Rating6A (AC), 4A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Package | - |
| Switch Function Current Rating Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Termination Style Panel Mount Termination Style Vire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection - Features Epoxy Sealed Terminals | Series | M |
| Current Rating 6A (AC), 4A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Circuit | 4PDT |
| Voltage Rating - AC Voltage Rating - DC 30V Actuator Type Standard Round 12.27mm Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection Features 125V 30V Standard Round Non-Illumination Non-Illuminated 12.27mm Non-Illuminated Panel Mount Wire Wrap Panel Mount Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals | Switch Function | On-On |
| Voltage Rating - DC30VActuator TypeStandard RoundActuator Length12.27mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Current Rating | 6A (AC), 4A (DC) |
| Actuator Type Actuator Length 12.27mm Illumination Non-Illuminated Illumination Type, Color | Voltage Rating - AC | 125V |
| Actuator Length Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Epoxy Sealed Terminals | Voltage Rating - DC | 30V |
| IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleWire WrapPanel Cutout DimensionsCircular - 6.50mm DiaBushing Thread1/4-40Ingress Protection-FeaturesEpoxy Sealed Terminals | Actuator Type | Standard Round |
| Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Actuator Length | 12.27mm |
| Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination | Non-Illuminated |
| Mounting Type Panel Mount Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination Type, Color | - |
| Termination Style Wire Wrap Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread 1/4-40 Ingress Protection - Features Epoxy Sealed Terminals | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions Circular - 6.50mm Dia Bushing Thread Ingress Protection Features Circular - 6.50mm Dia 1/4-40 Epoxy Sealed Terminals | Mounting Type | Panel Mount |
| Bushing Thread 1/4-40 Ingress Protection Features Epoxy Sealed Terminals | Termination Style | Wire Wrap |
| Ingress Protection - Epoxy Sealed Terminals | Panel Cutout Dimensions | Circular - 6.50mm Dia |
| Features Epoxy Sealed Terminals | Bushing Thread | 1/4-40 |
| | Ingress Protection | - |
| Report errors? | Features | Epoxy Sealed Terminals |
| | | Report errors? |

M2042SA1W08 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2042SA1W08 Payment Methods



















M2042SA1W08 Shipping Methods













If you have any question about M2042SA1W08, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com