



M2112TCFW13 Information

Heisener.com

Part Number M2112TCFW13
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2112TCFW13 Specifications

Manufacturer Part Number Manufacturer NKK Switches Switches Toggle Switches Package Series M2100 Circuit SPDT Switch Function On-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Illumination Illumination Illumination Type, Color Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Panel Cutout Dimensions Bushing Thread Ingress Protection Features Epoxy Sealed Terminals Report errors?		
CategorySwitchesPackage-SeriesM2100CircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Manufacturer Part Number	M2112TCFW13
Package - Series M2100 Circuit SPDT Switch Function On-On Current Rating AC 125V Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round 14.70mm Illumination Illumination Illumination Type, Color LED, Red/Green Illumination Type, Color LED, Red/Green Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Sundard Cutout Dimensions - S	Manufacturer	NKK Switches
Package-SeriesM2100CircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Category	Switches
SeriesM2100CircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125 VVoltage Rating - DC30 VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Package	-
Switch FunctionOn-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Series	M2100
Current Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Circuit	SPDT
Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length14.70mmIlluminationIlluminatedIllumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Switch Function	On-On
Voltage Rating - DC Actuator Type Standard Round Actuator Length 14.70mm Illumination Illuminated Illumination Type, Color LED, Red/Green Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features Epoxy Sealed Terminals	Current Rating	6A (AC), 3A (DC)
Actuator Type Actuator Length 14.70mm Illumination Illuminated Illumination Type, Color Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Through Hole Termination Style Panel Cutout Dimensions Panel Cutout Dimensions Unthreaded Ingress Protection Features Standard Round 14.70mm Illumination Style Illuminated Illuminated Illuminated Illuminated Ingress Protection Features Standard Round 14.70mm Illuminated Illumina	Voltage Rating - AC	125V
Actuator Length 14.70mm Illumination Illuminated Illumination Type, Color LED, Red/Green Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Voltage Rating - DC	30V
Illumination Illuminated Illumination Type, Color LED, Red/Green Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Actuator Type	Standard Round
Illumination Type, ColorLED, Red/GreenIllumination Voltage (Nominal)1.7, 2 VDCMounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Actuator Length	14.70mm
Illumination Voltage (Nominal) 1.7, 2 VDC Mounting Type Through Hole PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection Features 1.7, 2 VDC Through Hole PC Pin Panel Cutout Dimensions - Epoxy Sealed Terminals	Illumination	Illuminated
Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesEpoxy Sealed Terminals	Illumination Type, Color	LED, Red/Green
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Illumination Voltage (Nominal)	1.7, 2 VDC
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Mounting Type	Through Hole
Bushing Thread Unthreaded Ingress Protection - Features Epoxy Sealed Terminals	Termination Style	PC Pin
Ingress Protection - Epoxy Sealed Terminals	Panel Cutout Dimensions	-
Features Epoxy Sealed Terminals	Bushing Thread	Unthreaded
	Ingress Protection	-
Report errors?	Features	Epoxy Sealed Terminals
· ·		Report errors?

M2112TCFW13 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2112TCFW13 Payment Methods



















M2112TCFW13 Shipping Methods













If you have any question about M2112TCFW13, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com