

### **M22-FG-T1 Information**



For Reference Only

Part Number M22-FG-T1

Manufacturer Omron Automation and Safety

**Category** Optoelectronics

Panel Indicators, Pilot Lights

**Description** PILOT LIGHT 110V LED ROUND GREEN

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **M22-FG-T1 Specifications**

Manufacturer Part Number         M22-FG-TI           Manufacturer         Omron Automation and Safety           Category         Optoelectronies           Panel Indicators, Pilot Lights           Package         -           Scries         M22           Type         LED           Lamp Color         Green           Lens Color         Green           Lens Transparency         Diffused           Ratings         AC           Voltage         100V           Current         -           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.88" (22.35mm)           Lens Style/Size         Round with Flat Top, 29.70mm           Millicandela Rating         -           Wavelength - Peak         -           Viewing Angle         -           Termination Style         -           Ingress Protection         IP65           Features         -           Report errors?		
Category  Package  Package  Series  M22  Type  LED  Lamp Color  Lens Color  Lens Transparency  Diffused  Ratings  AC  Voltage  100V  Current  Panel Cutout Shape  Panel Cutout Dimensions  Lens Style/Size  Mound  Millicandela Rating  Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  Omega  Lindicators, Pilot Lights  Panel Cutout Lights  AC  U22  Green  LED  Green  Green  JUffused  AC  AC  AC  Voltage  100V  Round  Name  Round  Panel Cutout Shape  Round  Wavelength - Peak  Viewing Angle  -  Termination Style  Ingress Protection  Features  Option Lights  AC  AC  AC  AC  AC  AC  AC  AC  AC  A	Manufacturer Part Number	M22-FG-T1
Package-SeriesM22TypeLEDLamp ColorGreenLens ColorGreenLens TransparencyDiffusedRatingsACVoltage100VCurrent-Panel Cutout ShapeRoundPanel Cutout Dimensions0.88" (22.35mm)Lens Style/SizeRound with Flat Top, 29.70mmMillicandela Rating-Viewing Angle-Termination Style-Ingress ProtectionIP65Features-	Manufacturer	Omron Automation and Safety
Package         -           Series         M22           Type         LED           Lamp Color         Green           Lens Color         Green           Lens Transparency         Diffused           Ratings         AC           Voltage         100V           Current         -           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.88" (22.35mm)           Lens Style/Size         Round with Flat Top, 29.70mm           Millicandela Rating         -           Wavelength - Peak         -           Viewing Angle         -           Termination Style         -           Ingress Protection         IP65           Features         -	Category	Optoelectronics
Series         M22           Type         LED           Lamp Color         Green           Lens Color         Green           Lens Transparency         Diffused           Ratings         AC           Voltage         100V           Current         -           Panel Cutout Shape         Round           Panel Cutout Dimensions         0.88" (22.35mm)           Lens Style/Size         Round with Flat Top, 29.70mm           Millicandela Rating         -           Wavelength - Peak         -           Viewing Angle         -           Termination Style         -           Ingress Protection         IP65           Features         -		Panel Indicators, Pilot Lights
TypeLEDLamp ColorGreenLens ColorGreenLens TransparencyDiffusedRatingsACVoltage100VCurrent-Panel Cutout ShapeRoundPanel Cutout Dimensions0.88" (22.35mm)Lens Style/SizeRound with Flat Top, 29.70mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination Style-Ingress ProtectionIP65Features-	Package	-
Lamp Color Lens Color Green Lens Transparency Diffused Ratings AC Voltage 100V Current - Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Flat Top, 29.70mm Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Ingress Protection Features Green G	Series	M22
Lens ColorGreenLens TransparencyDiffusedRatingsACVoltage100VCurrent-Panel Cutout ShapeRoundPanel Cutout Dimensions0.88" (22.35mm)Lens Style/SizeRound with Flat Top, 29.70mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination Style-Ingress ProtectionIP65Features-	Type	LED
Lens TransparencyDiffusedRatingsACVoltage100VCurrent-Panel Cutout ShapeRoundPanel Cutout Dimensions0.88" (22.35mm)Lens Style/SizeRound with Flat Top, 29.70mmMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination Style-Ingress ProtectionIP65Features-	Lamp Color	Green
Ratings AC  Voltage 100V  Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.88" (22.35mm)  Lens Style/Size Round with Flat Top, 29.70mm  Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style - Ingress Protection IP65  Features -	Lens Color	Green
Voltage 100V  Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.88" (22.35mm)  Lens Style/Size Round with Flat Top, 29.70mm  Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style - Ingress Protection IP65  Features -	Lens Transparency	Diffused
Current - Round Round - Round - O.88" (22.35mm)  Lens Style/Size Round with Flat Top, 29.70mm  Millicandela Rating - Viewing Angle - Termination Style Ingress Protection IP65  Features - Features - Current Round - Features - Featur	Ratings	AC
Panel Cutout Dimensions  0.88" (22.35mm)  Lens Style/Size  Round with Flat Top, 29.70mm  Millicandela Rating  - Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  Round  - Round	Voltage	100V
Panel Cutout Dimensions  Lens Style/Size  Round with Flat Top, 29.70mm  Millicandela Rating  - Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  0.88" (22.35mm)  Round with Flat Top, 29.70mm  -  Ingress Protection  IP65	Current	-
Lens Style/Size Round with Flat Top, 29.70mm  Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style - Ingress Protection IP65 Features -	Panel Cutout Shape	Round
Millicandela Rating  Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  -  Ingress Protection	Panel Cutout Dimensions	0.88" (22.35mm)
Wavelength - Peak  Viewing Angle  Termination Style  Ingress Protection  Features  -  Ingress Protection  IP65  -  -  -  -  -  -  -  -  -  -  -  -  -	Lens Style/Size	Round with Flat Top, 29.70mm
Viewing Angle-Termination Style-Ingress ProtectionIP65Features-	Millicandela Rating	-
Termination Style - Ingress Protection IP65 Features -	Wavelength - Peak	-
Ingress Protection IP65 Features -	Viewing Angle	-
Features -	Termination Style	-
	Ingress Protection	IP65
Report errors?	Features	-
		Report errors?

### **M22-FG-T1 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **M22-FG-T1 Payment Methods**





















### **M22-FG-T1 Shipping Methods**













If you have any question about M22-FG-T1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com