

# M24308/23-2F

#### M24308/23-2F Information

Heisener.com	M24308/23-2F TE Connectivity Aerospace, Defense and Marine Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 15POS VERT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### M24308/23-2F Specifications

Manufacturer     TE Connectivity Aerospace, Defense and Marine       Category     Connectors, Interconnects       D-Sub Connectors     D-Sub Connectors       Package     -       Series     Military, MIL-DTL-24308, AMPLIMITE 109       Connector Style     D-Sub Connectors       Connector Type     Receptacle, Female Sockets       Number of Positions     15       Number of Rows     2       Shell Size, Connector Layout     2 (DA, A)       Contact Type     Signal       Mounting Type     Through Hole       Flange Feature     Solder       Features     -       Shell Material, Finish     Stel, Cadmium Plated       Contact Finish Thickness     Iopin (0.25µm)		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Manufacturer Part Number	M24308/23-2F
D-Sub ConnectorsPackage-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeHousing/Shell (Unthreaded)Flange FeatureSolderFeatures-Shell Material, FinishSidel, Cadmium PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Metrial Flammability Rating-Stell Flammability Rating-	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Material Flammability Rating-		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Series	Military, MIL-DTL-24308, AMPLIMITE 109
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishIojuin (0.25µm)Ingress Protection-Material Flammability Rating-	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness1/uin (0.25µm)Ingress Protection-Aderial Flammability Rating-	Number of Positions	15
Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Number of Rows	2
Mounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Contact Type	Signal
TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Mounting Type	Through Hole
Features-Features-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Termination	Solder
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Features	-
Contact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Shell Material, Finish	Steel, Cadmium Plated
Ingress Protection -   Material Flammability Rating -	Contact Finish	Gold
Material Flammability Rating -	Contact Finish Thickness	10µin (0.25µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	-
		Report errors?

#### M24308/23-2F Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### M24308/23-2F Payment Methods



## M24308/23-2F Shipping Methods



If you have any question about M24308/23-2F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com