

## M24308/23-4F

#### M24308/23-4F Information

Heisener.com	M24308/23-4F TE Connectivity Aerospace, Defense and Marine Connectors, Interconnects D-Sub Connectors CONN D-SUB RCPT 37POS VERT SLDR - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## M24308/23-4F Specifications

ManufacturerTE Connectivity Aerospace, Defense and MarineCategoryConnectors, InterconnectsD-Sub ConnectorsD-Sub ConnectorsPackage-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish ThicknessIopin (0.25µm)Ingress Protection-		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Manufacturer Part Number	M24308/23-4F
D-Sub ConnectorsPackage-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact FinishJupin (0.25µm)Ingress Protection-Material Flammability Rating-	Manufacturer	TE Connectivity Aerospace, Defense and Marine
Package-SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Cadmium PlatedContact FinishGoldContact Finish Thickness-Ingress Protection-Metrial Flammability Rating-	Category	Connectors, Interconnects
SeriesMilitary, MIL-DTL-24308, AMPLIMITE 109Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishStel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Atterial Flammability Rating-	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish ThicknessI0µin (0.25µm)Ingress Protection-Material Flammability Rating-	Series	Military, MIL-DTL-24308, AMPLIMITE 109
Number of Positions37Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishIopµin (0.25µm)Ingress Protection-Material Flammability Rating-	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact Finish ThicknessIoµin (0.25µm)Ingress Protection-Material Flammability Rating-	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C)Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Adderial Flammability Rating-	Number of Positions	37
Contact TypeSignalMounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Atterial Flammability Rating-	Number of Rows	2
Mounting TypeThrough HoleFlange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Shell Size, Connector Layout	4 (DC, C)
Flange FeatureHousing/Shell (Unthreaded)TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Contact Type	Signal
TerminationSolderFeatures-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Mounting Type	Through Hole
Features-Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Flange Feature	Housing/Shell (Unthreaded)
Shell Material, FinishSteel, Cadmium PlatedContact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Termination	Solder
Contact FinishGoldContact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Features	-
Contact Finish Thickness10µin (0.25µm)Ingress Protection-Material Flammability Rating-	Shell Material, Finish	Steel, Cadmium Plated
Ingress Protection -   Material Flammability Rating -	Contact Finish	Gold
Material Flammability Rating -	Contact Finish Thickness	10µin (0.25µm)
	Ingress Protection	-
Report errors?	Material Flammability Rating	-
		Report errors?

#### M24308/23-4F Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE GUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### M24308/23-4F Payment Methods



### M24308/23-4F Shipping Methods



If you have any question about M24308/23-4F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com