



M27W101-80K6 Information

Heisener.com

For Reference Only

Part Number M27W101-80K6 Manufacturer STMicroelectronics Category Integrated Circuits (ICs)

Memory

Description IC OTP 1MBIT 80NS 32PLCC

Package 32-LCC (J-Lead)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M27W101-80K6 Specifications

Manufacturer Part Number M27W101-80K6 Manufacturer STMicroelectronics Category Integrated Circuits (ICs) Memory Memory Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format EPROM Technology EPROM - OTP Memory Size IMb (128K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page - Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	•	
Category Integrated Circuits (ICs) Memory Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format EPROM Technology EPROM - OTP Memory Size IMb (128K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page Access Time 80ns Voltage - Supply Operating Temperature Auchon Size Integrated Circuits (ICs) Memory 82-LCC (J-Lead) Memory Surface Mount Package / Case 32-LCC (J-Lead)	Manufacturer Part Number	M27W101-80K6
Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format EPROM Technology EPROM - OTP Memory Size 1Mb (128K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page - Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Manufacturer	STMicroelectronics
Package 32-LCC (J-Lead) Series - Memory Type Non-Volatile Memory Format EPROM Technology EPROM - OTP Memory Size 1Mb (128K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page - Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Category	Integrated Circuits (ICs)
Series - Memory Type Non-Volatile Memory Format EPROM Technology EPROM - OTP Memory Size 1Mb (128K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page - Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)		Memory
Memory TypeNon-VolatileMemory FormatEPROMTechnologyEPROM - OTPMemory Size1Mb (128K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time80nsVoltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Package	32-LCC (J-Lead)
Memory FormatEPROMTechnologyEPROM - OTPMemory Size1Mb (128K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time80nsVoltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Series	-
Technology EPROM - OTP Memory Size 1Mb (128K x 8) Memory Interface Parallel Clock Frequency - Write Cycle Time - Word, Page Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature 40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Memory Type	Non-Volatile
Memory Size1Mb (128K x 8)Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time80nsVoltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Memory Format	EPROM
Memory InterfaceParallelClock Frequency-Write Cycle Time - Word, Page-Access Time80nsVoltage - Supply2.7 V ~ 3.6 VOperating Temperature-40°C ~ 85°C (TA)Mounting TypeSurface MountPackage / Case32-LCC (J-Lead)	Technology	EPROM - OTP
Clock Frequency Write Cycle Time - Word, Page Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Memory Size	1Mb (128K x 8)
Write Cycle Time - Word, Page Access Time 80ns Voltage - Supply 2.7 V ~ 3.6 V Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Memory Interface	Parallel
Access Time $80ns$ Voltage - Supply $2.7 \text{ V} \sim 3.6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C} \text{ (TA)}$ Mounting TypeSurface MountPackage / Case 32-LCC (J-Lead)	Clock Frequency	-
Voltage - Supply $2.7 \text{ V} \sim 3.6 \text{ V}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C (TA)}$ Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Write Cycle Time - Word, Page	-
Operating Temperature -40°C ~ 85°C (TA) Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Access Time	80ns
Mounting Type Surface Mount Package / Case 32-LCC (J-Lead)	Voltage - Supply	2.7 V ~ 3.6 V
Package / Case 32-LCC (J-Lead)	Operating Temperature	-40°C ~ 85°C (TA)
	Mounting Type	Surface Mount
0 1' D ' D 1	Package / Case	32-LCC (J-Lead)
Supplier Device Package 32-PLCC (11.35x13.89)	Supplier Device Package	32-PLCC (11.35x13.89)
Report errors?		Report errors?

M27W101-80K6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M27W101-80K6 Payment Methods



















M27W101-80K6 Shipping Methods













If you have any question about M27W101-80K6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com