



M2T12SA5G03/U Information



For Reference Only

Part Number M2T12SA5G03/U
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE SPDT 0.4VA 28V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2T12SA5G03/U Specifications

| Manufacturer Part Number M2T12SA5G03/U Manufacturer NKK Switches Category Switches Package - Series M2 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | | |
|--|--------------------------------|-----------------|
| Category Switches Package - Series M2 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Manufacturer Part Number | M2T12SA5G03/U |
| Package - Series M2 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Manufacturer | NKK Switches |
| Package - Series M2 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Category | Switches |
| Series M2 Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | | Toggle Switches |
| Circuit SPDT Switch Function On-On Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Package | - |
| Switch FunctionOn-OnCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Series | M2 |
| Current Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Circuit | SPDT |
| Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Switch Function | On-On |
| Voltage Rating - DC28VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Current Rating | 0.4VA (AC/DC) |
| Actuator Type Standard Round 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Voltage Rating - AC | 28V |
| Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Voltage Rating - DC | 28V |
| IlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Actuator Type | Standard Round |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Actuator Length | 12.70mm |
| Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Illumination | Non-Illuminated |
| Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Illumination Type, Color | - |
| Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Mounting Type | Through Hole |
| Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Termination Style | PC Pin |
| Ingress Protection - Features Process Sealed | Panel Cutout Dimensions | - |
| Features Process Sealed | Bushing Thread | Unthreaded |
| | Ingress Protection | - |
| Report errors? | Features | Process Sealed |
| | | Report errors? |

M2T12SA5G03/U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2T12SA5G03/U Payment Methods



















M2T12SA5G03/U Shipping Methods













If you have any question about M2T12SA5G03/U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com