



M2T13SA5W03/U Information

Heisener.com

Part Number M2T13SA5W03/U Manufacturer NKK Switches

Category Switches
Toggle Switches

Description SWITCH TOGGLE SPDT 6A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2T13SA5W03/U Specifications

| Manufacturer Part Number Manufacturer NKK Switches Switches Toggle Switches Package Series M2 Circuit SPDT Switch Function Current Rating 6A (AC), 3A (DC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole Panel Cutout Dimensions Bushing Thread Ingress Protection Features Process Sealed Report errors? | | |
|--|--------------------------------|------------------|
| CategorySwitchesPackage-SeriesM2CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Manufacturer Part Number | M2T13SA5W03/U |
| Package - Circuit SPDT Switch Function On-Off-On Current Rating | Manufacturer | NKK Switches |
| Package - Series M2 Circuit SPDT Switch Function On-Off-On Current Rating 6A (AC), 3A (DC) Voltage Rating - AC 125V Voltage Rating - DC 30V Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Category | Switches |
| SeriesM2CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | | Toggle Switches |
| CircuitSPDTSwitch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Package | - |
| Switch FunctionOn-Off-OnCurrent Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Series | M2 |
| Current Rating6A (AC), 3A (DC)Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Circuit | SPDT |
| Voltage Rating - AC125VVoltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Switch Function | On-Off-On |
| Voltage Rating - DC30VActuator TypeStandard RoundActuator Length12.70mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Current Rating | 6A (AC), 3A (DC) |
| Actuator Type Standard Round Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Voltage Rating - AC | 125V |
| Actuator Length 12.70mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Voltage Rating - DC | 30V |
| Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Actuator Type | Standard Round |
| Illumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Actuator Length | 12.70mm |
| Illumination Voltage (Nominal)-Mounting TypeThrough HoleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-FeaturesProcess Sealed | Illumination | Non-Illuminated |
| Mounting Type Through Hole Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Illumination Type, Color | - |
| Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Illumination Voltage (Nominal) | - |
| Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Sealed | Mounting Type | Through Hole |
| Bushing Thread Unthreaded Ingress Protection Features Process Sealed | Termination Style | PC Pin |
| Ingress Protection - Process Sealed Process Sealed | Panel Cutout Dimensions | - |
| Features Process Sealed | Bushing Thread | Unthreaded |
| | Ingress Protection | - |
| Report errors? | Features | Process Sealed |
| L. Control of the con | | Report errors? |

M2T13SA5W03/U Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2T13SA5W03/U Payment Methods



















M2T13SA5W03/U Shipping Methods













If you have any question about M2T13SA5W03/U, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com