



M2T25S4A5G30 Information

Heisener.com

Part Number M2T25S4A5G30
Manufacturer NKK Switches
Category Switches

Toggle Switches

Description SWITCH TOGGLE DPDT 0.4VA 28V

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M2T25S4A5G30 Specifications

Manufacturer Part Number M2T2584A5G30 Manufacturer NKK Switches Category Switches Package - Series M2 Circuit DPDT Switch Function On-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Features Process Staled		
CategorySwitchesPackage-SeriesM2CircuitDPDTSwitch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Manufacturer Part Number	M2T25S4A5G30
Package - Circuit DPDT Switch Function On-Mom Current Rating O.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Type, Color - Illumination Voltage (Nominal) Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style Panel Cutout Dimensions Bushing Thread Unthreaded Ingress Protection - Unthreaded Ingress Protection - Circum Care Care Care Care Care Care Care Care	Manufacturer	NKK Switches
Package - Series M2 Circuit DPDT Switch Function On-Mom Current Rating 0.4VA (AC/DC) Voltage Rating - AC 28V Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Category	Switches
SeriesM2CircuitDPDTSwitch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-		Toggle Switches
CircuitDPDTSwitch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Package	-
Switch FunctionOn-MomCurrent Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Series	M2
Current Rating0.4VA (AC/DC)Voltage Rating - AC28VVoltage Rating - DC28VActuator TypeStandard RoundActuator Length7.62mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypeThrough Hole, Right AngleTermination StylePC PinPanel Cutout Dimensions-Bushing ThreadUnthreadedIngress Protection-	Circuit	DPDT
Voltage Rating - AC Voltage Rating - DC 28V Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection - Unthreaded Ingress Protection	Switch Function	On-Mom
Voltage Rating - DC Actuator Type Standard Round 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection - Standard Round 7.62mm Non-Illuminated - Unthreaded Ingress Protection - - - - - - - - - - - - -	Current Rating	0.4VA (AC/DC)
Actuator Type Standard Round Actuator Length 7.62mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Voltage Rating - AC	28V
Actuator Length Through Hole, Right Angle Termination Style Panel Cutout Dimensions Bushing Thread Ingress Protection 7.62mm Non-Illuminated Non-Illuminated - Through Hole, Right Angle PC Pin - Unthreaded Ingress Protection - Through Hole, Right Angle PC Pin - Unthreaded	Voltage Rating - DC	28V
Illumination Non-Illuminated Illumination Type, Color	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Ingress Protection - Color Line Angle Line Angle PC Pin Line Angle Line Angle	Actuator Length	7.62mm
Illumination Voltage (Nominal) Mounting Type Through Hole, Right Angle PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection - Unthreaded	Illumination	Non-Illuminated
Mounting Type Through Hole, Right Angle Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Illumination Type, Color	-
Termination Style PC Pin Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions - Bushing Thread Unthreaded Ingress Protection -	Mounting Type	Through Hole, Right Angle
Bushing Thread Unthreaded Ingress Protection -	Termination Style	PC Pin
Ingress Protection -	Panel Cutout Dimensions	-
	Bushing Thread	Unthreaded
Features Process Seeled	Ingress Protection	-
Teatures 1 rocess search	Features	Process Sealed
Report errors?		Report errors?

M2T25S4A5G30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M2T25S4A5G30 Payment Methods



















M2T25S4A5G30 Shipping Methods













If you have any question about M2T25S4A5G30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com