

# M39003/03-0143

#### M39003/03-0143 Information

Heisener.com	 M39003/03-0143 Vishay Sprague Capacitors Tantalum Capacitors CAP TANT 270UF 10% 15V AXIAL Axial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### M39003/03-0143 Specifications

Manufacturer Part Number       M39003/03-0143         Manufacturer       Vishay Sprague         Category       Capacitors         Tantalum Capacitors       Tantalum Capacitors         Package       Axial         Series       Military, MIL-PRF-39003/3, CSR23         Capacitance       270µF         Tolerance       ±10%         Voltage - Rated       5V         System       Hermetically Sealed         Voltage - Rated       5V         System       Ses C = 125°C         Lifetime @ Temp.       -         Mounting Type       Siste C = 125°C         Nounting Type       Axial         Size / Dimension       Siste C = 125°C         Lifetime @ Temp.       -         Package / Case       Axial         Size / Dimension       Siste / Dimension         Height - Seated (Max)       -         Lead Spacing       -         Manufacturer Size Code       D         Features       Military         Height - Seated (Max)       -         Life Agae       Military		
CategoryCapacitorsTatalun CapacitorsPackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance270µFColerance±10%Voltage - Rated55YpeHernetically SealedSty-Operating Temperature-Operating TypeSon CaraceNunting Type-Package / Case-Size / Dimension0.51° Dia x 0.78° L (8.92mm x 19.96mm)Steid Maxing-Height - Seated (Max)-Lead Spacing-Mundracturer Size CodeDFaeturesMilitary <td>Manufacturer Part Number</td> <td>M39003/03-0143</td>	Manufacturer Part Number	M39003/03-0143
Initialum CapacitorsPackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance270μFCapacitance±10%Tolerance±10%Voltage - Rated15VTypeHermetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351° Dia x 0.786° L (8.92mm x 19.96mm)Height - Seated (Max)-Lead SpacingDAnufacturer Size CodeDFaturesMilitaryFaturesMilitary	Manufacturer	Vishay Sprague
PackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance270µFTolerance±10%Voltage - Rated±10%Voltage - Rated15VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ Temp.Through HoleNounting TypeMilitary Otage - MaxiaSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead SpacingDManufacturer Size CodeMilitaryFaturesMilitaryFaturesMilitaryFature RateMilitary	Category	Capacitors
Series       Military, MIL-PRF-39003/3, CSR23         Capacitance       270μF         Capacitance       ±10%         Tolerance       ±10%         Voltage - Rated       15V         Type       Hermetically Sealed         ESR (Equivalent Series Resistance)       -         Operating Temperature       -55°C ~ 125°C         Lifetime @ Temp.       -         Mounting Type       Through Hole         Package / Case       Axial         Size / Dimension       0.351" Dia x 0.786" L (8.92mm x 19.96mm)         Height - Seated (Max)       -         Lead Spacing       -         Manufacturer Size Code       D         Features       Military         Failure Rate       M(1%)		Tantalum Capacitors
Capacitance270µFTolerance±10%Voltage - Rated15VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / DimensionHeight - Seated (Max)-Lead Spacing-FeaturesDFeatures ReteMilitaryFeaturesMilitaryFeaturesM(1%)	Package	Axial
Tolerance±10%Voltage - Rated15VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeMinogi HolePackage / CaseAxialSize / Dimension-Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateMi(%)	Series	Military, MIL-PRF-39003/3, CSR23
NumberNumberVoltage - Rated15VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead SpacingDFeaturesMilitaryFeaturesMilitaryFailure RateM (1%)	Capacitance	270µF
TypeHermetically SealedFSR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMiltaryFailure RateM (1%)	Tolerance	$\pm 10\%$
ESR (Equivalent Series Resistance)-ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFully RateM (1%)	Voltage - Rated	15V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM (1%)	Туре	Hermetically Sealed
Lifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM(1%)	ESR (Equivalent Series Resistance)	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM(1%)	Operating Temperature	-55°C ~ 125°C
Package / CaseAxialSize / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM (1%)	Lifetime @ Temp.	-
Size / Dimension0.351" Dia x 0.786" L (8.92mm x 19.96mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM (1%)	Mounting Type	Through Hole
Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM(1%)	Package / Case	Axial
Lead Spacing-Manufacturer Size CodeDFeaturesMilitaryFailure RateM(1%)	Size / Dimension	0.351" Dia x 0.786" L (8.92mm x 19.96mm)
Manufacturer Size CodeDFeaturesMilitaryFailure RateM(1%)	Height - Seated (Max)	-
FeaturesMilitaryFailure RateM(1%)	Lead Spacing	-
Failure Rate M (1%)	Manufacturer Size Code	D
	Features	Military
	Failure Rate	M (1%)
Report errors?		Report errors?

#### M39003/03-0143 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### M39003/03-0143 Payment Methods



### M39003/03-0143 Shipping Methods



If you have any question about M39003/03-0143, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com