

M39003/03-0154

lest a Quote

M39003/03-0154 Information

Heisener.com	Part Number	M39003/03-0154	
	Manufacturer	Vishay Sprague	6
	Category	Capacitors Tantalum Capacitors	Ĭ
	Description	CAP TANT 56UF 10% 20V AXIAL	
	Package	Axial	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



M39003/03-0154 Specifications

Manufacturer Part NumberM39003/03-0154ManufacturerVishay SpragueCategoryCapacitorsTantalum CapacitorsTantalum CapacitorsPackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance56µFTolerance10%Voltage - Rated20VTypeHermetically SealedOperating Temperature-55°C ~ 125°CNouring TypeThrough HolePackage / CaseAxialSize / Dimension0.289° Dia x 0.686° L (7.34mm x 17.42mm)Height - Seated (Max)-Kanufacturer Size Code-Kanufacturer Size CodeKilturer		
CategoryCapacitorsPackageAxialPackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance56µFTolerance±10%Voltage - Rated20VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ Temp.Through HolePackage / CaseAxialSize / Dimension0.289° Dia x 0.686° L (7.34mm x 17.42mm)Height - Seated (Max)-Hanufacturer Size CodeC	Manufacturer Part Number	M39003/03-0154
Antalum CapacitorsPackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance56μFTolerance±10%Voltage - Rated20VTypeHermetically SealedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 125°CLifetime @ TempMounting TypeMinogh HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead SpacingC	Manufacturer	Vishay Sprague
PackageAxialSeriesMilitary, MIL-PRF-39003/3, CSR23Capacitance56µFTolerance±10%Voltage - Rated20VTypeHermetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempPackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lad SpacingCMunufacturer Size CodeC	Category	Capacitors
SeriesMilitary, MIL-PRF-39003/3, CSR23SeriesS6µFCapacitance£10%Tolerance±10%Voltage - Rated20VTypeHermetically SealedESR (Equivalent Series Resistance)-Operating Temperature55°C ~ 125°CLifetime @ TempPackage / CaseAxialSize / Dimension0.289° Dia x 0.686° L (7.34mm x 17.42mm)Height - Seated (Max)-Lad SpacingCMaunfacturer Size CodeC		Tantalum Capacitors
Capacitance56μFTolerance±10%Voltage - Rated20VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 125°CLifetime @ TempMounting TypeHrough HolePackage / CaseAxialSize / Dimension-Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Package	Axial
Tolerance±10%Voltage - Rated20VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289° Dia x 0.686° L (7.34mm x 17.42mm)Height - Seated (Max)-Lead SpacingGManufacturer Size CodeC	Series	Military, MIL-PRF-39003/3, CSR23
Voltage - Rated20VTypeHernetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead SpacingCManufacturer Size CodeC	Capacitance	56µF
TypeHermetically SealedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Tolerance	$\pm 10\%$
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Voltage - Rated	20V
Operating Temperature-55°C ~ 125°CLifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Туре	Hermetically Sealed
Lifetime @ TempMounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	ESR (Equivalent Series Resistance)	-
Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Operating Temperature	-55°C ~ 125°C
Package / CaseAxialSize / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Lifetime @ Temp.	-
Size / Dimension0.289" Dia x 0.686" L (7.34mm x 17.42mm)Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Mounting Type	Through Hole
Height - Seated (Max)-Lead Spacing-Manufacturer Size CodeC	Package / Case	Axial
Lead Spacing-Manufacturer Size CodeC	Size / Dimension	0.289" Dia x 0.686" L (7.34mm x 17.42mm)
Manufacturer Size Code C	Height - Seated (Max)	-
	Lead Spacing	-
Eastures Military	Manufacturer Size Code	С
reatures Minitary	Features	Military
Failure RateM (1%)	Failure Rate	M (1%)
Report errors		Report errors?

M39003/03-0154 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

M39003/03-0154 Payment Methods



M39003/03-0154 Shipping Methods



If you have any question about M39003/03-0154, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com