



M39014/021415 Information

Heisener.com

Part Number M39014/021415

Manufacturer Cornell Dubilier Electronics (CDE)

Category Capacitors

Ceramic Capacitors

Description CAP CER 1UF 50V 10% RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M39014/021415 Specifications

Manufacturer Part Number M39014/021415 Manufacturer Cornell Dubilier Electronics (CDE) Category Capacitors Package Radial Series Military, MIL-PRF-39014, CKR06 Capacitance 1μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm) Height Sexted (Max) 0.200" (7.36mm)		
Category Capacitors Package Radial Series Military, MIL-PRF-39014, CKR06 Capacitance 1μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Manufacturer Part Number	M39014/021415
PackageRadialSeriesMilitary, MIL-PRF-39014, CKR06Capacitance1μFTolerance±10%Voltage - Rated50VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialSeriesMilitary, MIL-PRF-39014, CKR06Capacitance1μFTolerance±10%Voltage - Rated50VTemperature CoefficientBXOperating Temperature-55°C ~ 125°CFeaturesMilitaryRatings-ApplicationsGeneral PurposeFailure RateR (0.01%)Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.290" L x 0.090" W (7.36mm x 2.28mm)	Category	Capacitors
Series Military, MIL-PRF-39014, CKR06 Capacitance 1μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)		Ceramic Capacitors
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Package	Radial
Tolerance $\pm 10\%$ Voltage - Rated $50V$ Temperature Coefficient BX Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension $0.290'' \text{ L x } 0.090'' \text{ W } (7.36\text{mm x } 2.28\text{mm})$	Series	Military, MIL-PRF-39014, CKR06
Voltage - Rated Temperature Coefficient BX Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 50V BX - -55°C ~ 125°C Military -6 Military -7 Military -7	Capacitance	1μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension BX Government Applications BX Military Applications General Purpose Radial Nounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension -55°C ~ 125°C Military Final Purpose Referral Purpose R (0.01%) Through Hole Package / Case Radial O.290" L x 0.090" W (7.36mm x 2.28mm)	Voltage - Rated	50V
Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Temperature Coefficient	BX
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension O.290" L x 0.090" W (7.36mm x 2.28mm)	Features	Military
Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Ratings	-
Mounting Type Through Hole Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Applications	General Purpose
Package / Case Radial Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Failure Rate	R (0.01%)
Size / Dimension 0.290" L x 0.090" W (7.36mm x 2.28mm)	Mounting Type	Through Hole
	Package / Case	Radial
Height Spated (May)	Size / Dimension	0.290" L x 0.090" W (7.36mm x 2.28mm)
neight - Sealed (Max) 0.290 (7.30mm)	Height - Seated (Max)	0.290" (7.36mm)
Thickness (Max)	Thickness (Max)	-
Lead Spacing 0.200" (5.08mm)	Lead Spacing	0.200" (5.08mm)
Lead Style Straight	Lead Style	Straight
Report errors		Report errors?

M39014/021415 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M39014/021415 Payment Methods





















M39014/021415 Shipping Methods













If you have any question about M39014/021415, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com