

M39014/05-2105 Information



For Reference Only

Part Number M39014/05-2105

Manufacturer KEMET Category Capacitors

Ceramic Capacitors

Description CAP CER 0.27UF 50V 10% AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M39014/05-2105 Specifications

Category Capacitors Package Axial Series Military, MIL-PRF-39014, CKR14 Capacitance 0.27µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing -		
Category Capacitors Package Axial Series Military, MIL-PRF-39014, CKR14 Capacitance 0.27µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	M39014/05-2105
Package Axial Series Military, MIL-PRF-39014, CKR14 Capacitance 0.27μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	KEMET
Package Axial Series Military, MIL-PRF-39014, CKR14 Capacitance 0.27μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series Military, MIL-PRF-39014, CKR14 Capacitance 0.27μF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.27µF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - The Mounting Type - Lead Style - Lead Style - Tolerance ±10% BR GOV Tolerance (No.01%) Aliance (Size / Dimension	Series	Military, MIL-PRF-39014, CKR14
Voltage - Rated Temperature Coefficient BR Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) Thickness (Max) Lead Spacing - Lead Style -	Capacitance	0.27μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style BR General Purpose Failure R (0.01%) General Purpose Failure Rate R (0.01%) General Purpose Failure Rate R (0.01%) General Purpose Failu	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style Since / Case -55°C ~ 125°C Military General Purpose General Purpose A (0.01%) General Purpose A	Voltage - Rated	50V
Features Military Ratings - Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Temperature Coefficient	BR
Ratings - General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - General Purpose	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) Thickness (Max) - Lead Spacing - Lead Style -	Features	Military
Failure Rate R (0.01%) Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case Axial Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	R (0.01%)
Size / Dimension 0.140" Dia x 0.390" L (3.56mm x 9.91mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.140" Dia x 0.390" L (3.56mm x 9.91mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

M39014/05-2105 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M39014/05-2105 Payment Methods



















M39014/05-2105 Shipping Methods













If you have any question about M39014/05-2105, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com