

M50-4301545

M50-4301545 Information

For Reference Only	www.heisener.com	Part Number Manufacturer Category	M50-4301545 Harwin Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	回 53%回 3974 - 34
	A STATE OF ST	Description	CONN RCPT 1.27MM SMD AU 30POS	P 39 1 -
		Package	-	ല്ലാത്ത്ത്ത്ത്
			For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com	Request a Quote
			E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



M50-4301545 Specifications

Manufacturer Part NumberM50-4301545ManufacturerHarwin Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesArcher M50Connector TypeReceptacleContact TypeReceptacleSorder Or SystemBoard to BoardNumber of Positions LoadedAllPitch - Mating0.050° (1.27mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypeSurface MountContact Finish - MatingGoldContact Finish Thickness - Mating-Solder ColorBackInsulation ColorBackInsulation FlexifiestSilarSulation Height0.181° (4.60mm)Contact Length - Post-Material Flammability RatineUL94 V-0		
CategoryConnectors - Headers, Receptacles, Female SocketsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesArcher M50Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.50° (1.27mm)Number of Rows2Row Spacing - MatingSolderYourd TypeSolderFerninationSolderContact Finish - MatingGoldContact Finish - Mating-Sudation ColorBlackInsulation ColorBlackInsulation Finish - Mating-Contact Finish - Mating-Contact Finish - Mating-Sudation Finish - Mating-Contact Finish - Mating-Contact Finish - Mating-Contact Finish - Mating-Sudation ColorBlackSudation Finish - Mating-Contact Finish - Mating-Contact Finish Thickness - Mating-Sudation Finish - Mating-Contact Finish - Mating-Contact Finish Thickness - Mating-Contact Finish Thickness - Mating-Contact Finish - Mating-Contact Finish - Mating-Contact Finish - Mating-Contact Finish - Mating-Contact Length - Post-Con	Manufacturer Part Number	M50-4301545
Indext Connectors - Headers, Receptacles, Female SocketsPackage-SeriesArcher M50Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.50° (1.27mm)Nouning TypeSolderYerminationSolderTerminationSolderStatening TypeSolderContact Finish F. MatingGoldContact Finish F. MatingGoldStatening TypeIsakanianSolderSolderStatening TypeSolderStatening TypeSolderContact Finish F. MatingSolderStatening TypeIsakanianSolderSolderStatening TypeSolderStatening	Manufacturer	Harwin Inc.
Package-SeriesArcher M50Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting Type0.050" (1.27mm)Yenning TypeSolderFarminationSolderFortaur TypeGoldContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature40°C ~ 105°C	Category	Connectors, Interconnects
SeriesArcher M50Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllPitch - Mating0.50° (1.27mm)Number of Rows2Row Spacing - Mating0.050° (1.27mm)Mounting TypeSurface MountTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldSundator ColorBlackInsulation Color0.181° (4.60mm)Contact Length - Post-Contact Length - Post-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllNumber of Rows2Number of Rows0.50° (1.27mm)Number of Rows0.50° (1.27mm)Mounting TypeSurface MountTerminationSolderFortant Finish - MatingSolderContact Finish - MatingGoldInsulation ColorBlackInsulation Finish - MatingI.81° (4.0mm)Fortaut Finish Thickness - MatingI.81° (4.0mm)Fortaut Finish - MatingI.81° (4.0mm)Fortaut Finish - PostI.81° (2.01°C°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Series	Archer M50
StyleBoard to BoardStyleBoard to BoardNumber of Positions30Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature40°C ~ 105°C	Connector Type	Receptacle
Number of Positions 30 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 2 Row Spacing - Mating 0.050" (1.27mm) Mounting Type 0.050" (1.27mm) Fermination Solder Fermination Solder Forter Finish - Mating Gold Contact Finish - Mating Gold Insulation Color Black Insulation Height 0.181" (4.60mm) Contact Length - Post - Operating Temperature 40°C ~ 105°C	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating.Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Style	Board to Board
Pitch - Mating0.050" (1.27mm)Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSurface MountFastening TypePosh-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.181" (4.60mm)Contact Length - Post40°C ~ 105°C	Number of Positions	30
Number of Rows2Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating0.050" (1.27mm)Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature40°C ~ 105°C	Pitch - Mating	0.050" (1.27mm)
Mounting TypeSurface MountTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Qperating Temperature40°C ~ 105°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature40°C ~ 105°C	Row Spacing - Mating	0.050" (1.27mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature40°C ~ 105°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Contact Finish - Mating	Gold
Insulation Height0.181" (4.60mm)Contact Length - Post-Operating Temperature-40°C ~ 105°C	Contact Finish Thickness - Mating	-
Contact Length - Post-Operating Temperature-40°C ~ 105°C	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.181" (4.60mm)
	Contact Length - Post	-
Material Flammability Rating UL94 V-0	Operating Temperature	$-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	6.5mm, 6.9mm
Ingress Protection	-
Features	Board Guide
	Demont among 2

Report errors?

M50-4301545 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about M50-4301545, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com