

M52-5013245 Information



For Reference Only

Part Number M52-5013245 Manufacturer Harwin Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description CONN RCPT 32POS T/H 1.27MM GOLD

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M52-5013245 Specifications

Manufacturer Part Number M52-5013245 Manufacturer Harwin Inc. Category Connectors, Interconnects Package - Series Archer M52 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C Material Flammability Rating UL94 V-0		
Category Connectors, Interconnects Package - Series Archer M52 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Manufacturer Part Number	M52-5013245
Package-SeriesArcher M52Connector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions32Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Manufacturer	Harwin Inc.
Package - Series Archer M52 Connector Type Receptacle Contact Type Forked Style Board to Board Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Category	Connectors, Interconnects
SeriesArcher M52Connector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions32Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeForkedStyleBoard to BoardNumber of Positions32Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Package	-
Contact TypeForkedStyleBoard to BoardNumber of Positions32Number of Positions LoadedAllPitch - Mating0.050" (1.27mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Series	Archer M52
Style Board to Board Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Connector Type	Receptacle
Number of Positions 32 Number of Positions Loaded All Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Contact Type	Forked
Number of Positions Loaded Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height Ontact Length - Post Operating Temperature All 0.050" (1.27mm)	Style	Board to Board
Pitch - Mating 0.050" (1.27mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Number of Positions	32
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.110" (2.79mm)Operating Temperature-40°C ~ 105°C	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.335" (8.51mm) Contact Length - Post Operating Temperature -40°C ~ 105°C	Pitch - Mating	0.050" (1.27mm)
Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.110" (2.79mm) Operating Temperature -40°C ~ 105°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.335"$ ($8.51mm$)Contact Length - Post $0.110"$ ($2.79mm$)Operating Temperature -40 °C ~ 105 °C	Contact Finish - Mating	Gold
Insulation Height $0.335" (8.51 mm)$ Contact Length - Post $0.110" (2.79 mm)$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Contact Finish Thickness - Mating	-
Contact Length - Post $0.110" (2.79 \text{mm})$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$	Insulation Height	0.335" (8.51mm)
	Contact Length - Post	0.110" (2.79mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-40°C ~ 105°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	-
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

M52-5013245 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M52-5013245 Payment Methods





















M52-5013245 Shipping Methods













If you have any question about M52-5013245, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com