



M5600-000005-300PG Information

Part Number M5600-000005-300PG

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

Description WIRELESS PRESSURE GAUGE 300PSI

Package Cylinder, Threaded

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M5600-000005-300PG Specifications

Manufacturer Part NumberM5600-00005-300PGManufacturerTE Connectivity Measurement SpecialtiesCategorySensors, TransducersPressure Sensors, TransducersPackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure600 PSI (4136.85 kPa)		
Category Sensors, Transducers Pressure Sensors, Transducers Cylinder, Threaded Series - Pressure Type Vented Gauge Operating Pressure 300 PSI (2068.43 kPa) Output Type Bluetooth Output 24 b Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style Sensors, Transducers Pressure Sensors, Transducers 1	Manufacturer Part Number	M5600-000005-300PG
Package Cylinder, Threaded Series - Pressure Type Vented Gauge Operating Pressure Output Type Bluetooth Output Output 4 b Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Tempination Style Pressure Sensors, Transducers Cylinder, Threaded Pressure Sensors, Transducers Cylinder, Threaded Fensors, Transducers Lensors, Transducers Vented Gauge Vented Gauge Vented Gauge Vented Gauge 200 PSI (2068.43 kPa) Bluetooth 24 b 40.25% Voltage - Supply Port Style Threaded Temperature Compensated Temperature Compensated	Manufacturer	TE Connectivity Measurement Specialties
PackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-	Category	Sensors, Transducers
Series-Pressure TypeVented GaugeOperating Pressure300 PSI (2068.43 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-		Pressure Sensors, Transducers
Pressure Type Operating Pressure 300 PSI (2068.43 kPa) Output Type Bluetooth Output 4 b Accuracy Voltage - Supply Port Size Male - 1/4" (6.35mm) NPT Port Style Features Temperature Compensated Termination Style	Package	Cylinder, Threaded
Operating Pressure 300 PSI (2068.43 kPa) Output Type Bluetooth Output 24 b Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style	Series	-
Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) NPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-	Pressure Type	Vented Gauge
Output 24 b Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style -	Operating Pressure	300 PSI (2068.43 kPa)
Accuracy $\pm 0.25\%$ Voltage - Supply $2.3 \text{ V} \sim 3.6 \text{ V}$ Port Size $Male - 1/4" (6.35 \text{mm}) \text{ NPT}$ Port Style $Threaded$ Features $Temperature Compensated$ Termination Style $-$	Output Type	Bluetooth
Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style -	Output	24 b
Port Size Male - 1/4" (6.35mm) NPT Port Style Threaded Features Temperature Compensated Termination Style -	Accuracy	±0.25%
Port Style Threaded Features Temperature Compensated Termination Style -	Voltage - Supply	2.3 V ~ 3.6 V
Features Temperature Compensated Termination Style -	Port Size	Male - 1/4" (6.35mm) NPT
Termination Style -	Port Style	Threaded
·	Features	Temperature Compensated
Maximum Pressure 600 PSI (4136.85 kPa)	Termination Style	-
000 101 (110000 111 11)	Maximum Pressure	600 PSI (4136.85 kPa)
Operating Temperature $-20^{\circ}\text{C} \sim 85^{\circ}\text{C}$	Operating Temperature	-20°C ~ 85°C
Package / Case Cylinder, Threaded	Package / Case	Cylinder, Threaded
Supplier Device Package -	Supplier Device Package	-
Report errors?		Report errors?

M5600-000005-300PG Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M5600-000005-300PG Payment Methods



















M5600-000005-300PG Shipping Methods













If you have any question about M5600-000005-300PG, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com