

M80-4113401 Information

Part Number M80-4113401 Manufacturer Harwin Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description 17+17 WAY FEMALE PC TAIL 4.5MM

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









M80-4113401 Specifications

Manufacturer Part Number M80-4113401 Manufacturer Harwin Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Datamate J-Tek Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating 12µin (0.30µm) Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm) Operating Temperature -55°C ~ 125°C		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Datamate J-Tek Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.181" (4.60mm)	Manufacturer Part Number	M80-4113401
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series Datamate J-Tek Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions All Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.181" (4.60mm)	Manufacturer	Harwin Inc.
Package - Series Datamate J-Tek Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating 12µin (0.30µm) Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Category	Connectors, Interconnects
SeriesDatamate J-TekConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Receptacle Contact Type Female Socket Style Board to Board or Cable Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish - Mating 12µin (0.30µm) Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Series	Datamate J-Tek
Style Board to Board or Cable Number of Positions 34 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating 12µin (0.30µm) Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Connector Type	Receptacle
Number of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Contact Type	Female Socket
Number of Positions Loaded Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Number of Positions	34
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Number of Rows	2
Termination Solder Fastening Type - Contact Finish - Mating Gold Contact Finish Thickness - Mating 12μin (0.30μm) Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating12μin (0.30μm)Insulation ColorBlackInsulation Height0.205" (5.20mm)Contact Length - Post0.181" (4.60mm)	Termination	Solder
Contact Finish Thickness - Mating 12μin (0.30μm) Insulation Color Black Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Fastening Type	-
Insulation Color Insulation Height O.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Contact Finish - Mating	Gold
Insulation Height 0.205" (5.20mm) Contact Length - Post 0.181" (4.60mm)	Contact Finish Thickness - Mating	12μin (0.30μm)
Contact Length - Post 0.181" (4.60mm)	Insulation Color	Black
	Insulation Height	0.205" (5.20mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Length - Post	0.181" (4.60mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead
Mated Stacking Heights	7.3mm, 7.55mm
Ingress Protection	-
Features	Mating Flange, Polarizing Key
	Report errors?

M80-4113401 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

M80-4113401 Payment Methods



















M80-4113401 Shipping Methods













If you have any question about M80-4113401, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com