

# M80-4122601

est a Quote

### M80-4122601 Information

	Part Number	M80-4122601
Contraction the sector of the	Manufacturer	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets
	Description	13+13 WAY FEMALE SMT + WO J/S
	Package	-
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# M80-4122601 Specifications

<table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-container><table-container><table-container><table-container><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row><table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-row></table-row></table-row></table-row></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container></table-container>		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesDatamate J-TekConnector TypeReceptacleContact TypeReceptacleContact TypeBoard to Board or CableNumber of Positions26Number of Positions LoadedAllNumber of Rows2Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of RowsSolderYerninationSolderFortinationSolderContact Finish - MatingGoldContact Finish - MatingIguin (0.30µm)Insulation ColorBlackInsulation Finish Thickness - MatingJiguin (0.30µm)Insulation Finish Thicknes - MatingIguin (0.30µm)Insulation Finish ThicknesIguin (0.30µm)Insulation Finish	Manufacturer Part Number	M80-4122601
Ackage .   Series Datamate J-Tek   Connector Type Receptacle   Contact Type Receptacle   Contact Type Board to Board or Cable   Style Board to Board or Cable   Number of Positions 26   Number of Positions Loaded All   Pitch - Mating 0.079" (2.00mm)   Number of Rows 2   Row Spacing - Mating 0.079" (2.00mm)   Mounting Type Surface Mount   Yernination Solder   Fastening Type -   Contact Finish - Mating Gold   Contact Finish Thickness - Mating Jujin (0.30µm)   Insulation Color Black   Insulation Height 0.220" (5.60mm)   Contact Length - Post -   Operating Temperature -55°C ~ 125°C	Manufacturer	Harwin Inc.
Package-SeriesDatamate J-TekConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - MatingIguin (3.0µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-SolderSolderSulation Height0.220" (5.60mm)Contact Length - Post-SolderSolderSulation Height0.5°C ~ 125°C	Category	Connectors, Interconnects
SeriesDatamate J-TekConnector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderTerminationSolderFastening Type-Contact Finish - MatingGoldNunder of Not1µin (0.3µm)Fastening Type-Contact Finish - Mating1µin (0.3µm)Insulation ColorBlackInsulation Height0.220" (5.00mm)Contact Length - Post-Operating Temperature-Sick - 125°C-		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeReceptacleContact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorJain (0.30µm)Insulation Height0.20" (5.60mm)Contact Length - Post-Contact Finish Post-Sulation Height0.20" (5.60mm)Contact Finish Post-Solder-Solder-SolderSolderSolder-Sold	Package	-
Contact TypeFemale SocketStyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldInsulation ColorBlackInsulation Height0.20" (5.00mm)Contact Length - Post-Contact Funsh ThotknesSilcerInsulation Height0.20" (5.00mm)Contact Length - Post-Contact Funsh Thotknes-Contact Funsh FunstSilcerInsulation Height0.20" (5.00mm)Contact Funsh - Post-Contact Funsh - Post	Series	Datamate J-Tek
StyleBoard to Board or CableNumber of Positions26Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldInsulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Contact Length - Post-Solder Schemen Sc	Connector Type	Receptacle
Number of Positions26Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldInsulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Solder- </td <td>Contact Type</td> <td>Female Socket</td>	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - MatingI2µin (0.30µm)Insulation ColorBlackInsulation Height0.20" (5.60mm)Contact Length - Post-Contact Length - Post-Solder-Solder-Contact Length - Post-Contact Fung Temperature-Solder-Contact Length - Post-Contact Solder-Contact Length - Post-Contact Solder-Contact Length - Post-Contact Solder-Contact Solder-Contact Solder-Contact Length - Post-Contact Solder-Contact Solder-Contact Length - Post-Contact Lengt	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Sore - 125°C-	Number of Positions	26
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - MatingI2µin (0.30µm)Insulation ColorBlackInsulation Height0.200" (5.60mm)Contact Length - Post-Song Contage Co	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeSurface MountTerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type-Contact Finish - MatingGoldContact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount
Contact Finish - MatingGoldContact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating12µin (0.30µm)Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Fastening Type	-
Insulation ColorBlackInsulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.220" (5.60mm)Contact Length - Post-Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	12µin (0.30µm)
Contact Length - Post-Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.220" (5.60mm)
	Contact Length - Post	-
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin-Lead
Mated Stacking Heights	7.7mm, 7.95mm
Ingress Protection	-
Features	Mating Flange, Polarizing Key

Report errors?

### M80-4122601 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about M80-4122601, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com