

# M8340104K1002FCD03

## M8340104K1002FCD03 Information

www.helsener.com	Part Number Manufacturer Category Description Package	M8340104K1002FCD03 Vishay Dale Resistors Resistor Networks, Arrays RES ARRAY 5 RES 10K OHM 6SIP 6-SIP For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# M8340104K1002FCD03 Specifications

CategoryResistorsResistor Networks, ArraysPackage6-SIPSeriesMilitary, MIL-PRF-83401/04, RZ040Circuit TypeBussedResistance (Ohms)10kTolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)		
CategoryResistorsResistor Networks, ArraysPackage6-SIPSeriesMilitary, MIL-PRF-83401/04, RZ040Circuit TypeBussedResistance (Ohms)10kTolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTomperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Manufacturer Part Number	M8340104K1002FCD03
Resistor Networks, ArraysPackage6-SIPSeriesMilitary, MIL-PRF-83401/04, RZ040Circuit TypeBussedResistance (Ohns)10kTolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTemperature Coefficient±100ppm°COperating Temperature55° < 125°C	Manufacturer	Vishay Dale
Package6-SIPSeriesMilitary, MIL-PRF-83401/04, RZ040Circuit TypeBussedResistance (Ohms)10kTolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTomperature Coefficient±100ppm°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Category	Resistors
Series Military, MIL-PRF-83401/04, RZ040   Series Bussed   Circuit Type Bussed   Resistance (Ohms) 10k   Tolerance ±1%   Number of Resistors 5   Number of Pins 6   Power Per Element 200mW   Tonperature Coefficient ±100ppm°C   Operating Temperature -55°C ~ 125°C   Applications Military   Mounting Type Through Hole   Supplier Device Package 6-SIP   Supplier Device Package 0.583" L x 0.098" W (14.81mm x 2.49mm)   Height - Seated (Max) 0.350" (8.89mm)		Resistor Networks, Arrays
Circuit TypeBussedResistance (Ohms)10kTolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Package	6-SIP
Resistance (Ohms)10kTolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Series	Military, MIL-PRF-83401/04, RZ040
Tolerance±1%Number of Resistors5Number of Pins6Power Per Element200mWTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Circuit Type	Bussed
Number of Resistors5Number of Pins6Power Per Element200mWTemperature Coefficient±100pm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Resistance (Ohms)	10k
Number of Pins6Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Tolerance	$\pm 1\%$
Power Per Element200mWTemperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Number of Resistors	5
Temperature Coefficient±100ppm/°COperating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Number of Pins	6
Operating Temperature-55°C ~ 125°CApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Power Per Element	200mW
ApplicationsMilitaryMounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Temperature Coefficient	±100ppm/°C
Mounting TypeThrough HolePackage / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Operating Temperature	-55°C ~ 125°C
Package / Case6-SIPSupplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Applications	Military
Supplier Device Package6-SIPSize / Dimension0.583" L x 0.098" W (14.81mm x 2.49mm)Height - Seated (Max)0.350" (8.89mm)	Mounting Type	Through Hole
Size / Dimension 0.583" L x 0.098" W (14.81mm x 2.49mm)   Height - Seated (Max) 0.350" (8.89mm)	Package / Case	6-SIP
Height - Seated (Max) 0.350" (8.89mm)	Supplier Device Package	6-SIP
•	Size / Dimension	0.583" L x 0.098" W (14.81mm x 2.49mm)
Report errors?	Height - Seated (Max)	0.350" (8.89mm)
		Report errors?

### M8340104K1002FCD03 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### M8340104K1002FCD03 Payment Methods



If you have any question about M8340104K1002FCD03, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com