



MA601C105KAA Information

Heisener.com

Part Number MA601C105KAA

Manufacturer AVX Corporation
Category Capacitors

Ceramic Capacitors

Description CAP CER 1UF 100V X7R AXIAL

Package Axia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MA601C105KAA Specifications

Manufacturer Part Number MA601C105KAA Manufacturer AVX Corporation Category Capacitors Package Axial Scries Ceralm? MA Capacitance 1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package Axial Series Ceralam? MA Capacitance 1µF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer Part Number	MA601C105KAA
Package Axial Series Ceralam? MA Capacitance 1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package Axial Series Ceralam? MA Capacitance 1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Category	Capacitors
Series Ceralam? MA Capacitance 1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1μF Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Package	Axial
Tolerance ±10% Voltage - Rated 100V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Ratings Applications General Purpose Failure Rate Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style	Series	Ceralam? MA
Voltage - Rated100VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.350" Dia x 0.690" L (8.89mm x 17.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Capacitance	1μF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.350" Dia x 0.690" L (8.89mm x 17.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeThrough HolePackage / CaseAxialSize / Dimension0.350" Dia x 0.690" L (8.89mm x 17.53mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Voltage - Rated	100V
Features - Ratings - Applications General Purpose General Purpose Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Chickness	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style - Case - Ca	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Ratings	-
Mounting Type Through Hole Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case Axial Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.350" Dia x 0.690" L (8.89mm x 17.53mm) Height - Seated (Max) - Thickness (Max) - Lead Spacing - Lead Style -	Mounting Type	Through Hole
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style -	Package / Case	Axial
Thickness (Max) - Lead Spacing - Lead Style -	Size / Dimension	0.350" Dia x 0.690" L (8.89mm x 17.53mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	-
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

MA601C105KAA Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MA601C105KAA Payment Methods



















MA601C105KAA Shipping Methods













If you have any question about MA601C105KAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com