

MAL202128108E3

MAL202128108E3 Information

	Aluminum Electrolytic Capacitors ption CAP ALUM 1UF 20% 63V AXIAL ge Axial, Can For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



MAL202128108E3 Specifications

ManufacturerVishay BC ComponentsCategoryCapacitorsAtuminum Electrolytic CapacitorsPackageAxial, CanSeries021 ASMCapacitance1µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzDiperating Temperature2500 Hrs @ 85°COperating Temperature64°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance55 OhmsLead Spacing0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseXial, Can	•	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageAxial, CanSeries021 ASMCapacitance1µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Pokage / CaseAxial, Can	Manufacturer Part Number	MAL202128108E3
Aluminum Electrolytic CapacitorsPackageAxial, CanSeries021 ASMCapacitanceμFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance55 OhmsLidad Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Manufacturer	Vishay BC Components
PackageAxial, CanSeries021 ASMCapacitance1µFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency12mA @ 100HzRipple Current - High Frequency-Impedance55 OhmsLiad Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Category	Capacitors
Series021 ASMCapacitanceμFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance55 OhmsLiad Spacing0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can		Aluminum Electrolytic Capacitors
CapacitanceμFTolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance55 OhmsLiad Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxia, Can	Package	Axial, Can
Tolerance±20%Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 100HzImpedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Series	021 ASM
Voltage - Rated63VESR (Equivalent Series Resistance)150 Ohm @ 100HzLifetime @ Temp.2500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 100HzRipple Current - High Frequency-Impedance55 OhmsLead Spacing0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeKaia, Can	Capacitance	lμF
Form 150 Ohm @ 100Hz Lifetime @ Temp. 2500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 12mA @ 100Hz Impedance - Lead Spacing - Size / Dimension 0.177" Diax 0.394" L (4.50mm x 10.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Axial, Can	Tolerance	±20%
Lifetime @ Temp.2500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 100HzRippe Current - High Frequency-Impedance55 OhmsLead Spacing0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Voltage - Rated	63V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 100HzRipple Current - High Frequency-Impedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	ESR (Equivalent Series Resistance)	150 Ohm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 100HzRipple Current - High Frequency-Impedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HoleAxial, Can-	Lifetime @ Temp.	2500 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency12mA @ 100HzRipple Current - High Frequency-Impedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency12mA @ 100HzRipple Current - High Frequency-Impedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance55 OhmsLead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Ripple Current - Low Frequency	12mA @ 100Hz
Lead Spacing-Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Ripple Current - High Frequency	-
Size / Dimension0.177" Dia x 0.394" L (4.50mm x 10.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Impedance	55 Ohms
Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Lead Spacing	-
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseAxial, Can	Size / Dimension	0.177" Dia x 0.394" L (4.50mm x 10.00mm)
Mounting TypeThrough HolePackage / CaseAxial, Can	Height - Seated (Max)	-
Package / Case Axial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Axial, Can
		Report errors?

MAL202128108E3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL202128108E3 Payment Methods



MAL202128108E3 Shipping Methods



If you have any question about MAL202128108E3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com