



MAL209735479E6 Information

Heisener.com

Part Number MAL209735479E6
Manufacturer Vishay BC Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 16V RADIAL

Package Radial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









MAL209735479E6 Specifications

Manufacturer Part Number MAL209735479E6 Manufacturer Vishay BC Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series 097 RLP 7 Capacitance 47µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	•	
Category Capacitors Package Radial, Can Series 097 RLP 7 Capacitance 47µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Manufacturer Part Number	MAL209735479E6
PackageRadial, CanSeries097 RLP 7Capacitance47μFTolerance±20%Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency59mA @ 120HzRipple Current - High Frequency-Impedance3.5 OhmsLead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Manufacturer	Vishay BC Components
Package Radial, Can Series 097 RLP 7 Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Category	Capacitors
Series 097 RLP 7 Capacitance 47µF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can		Aluminum Electrolytic Capacitors
Capacitance 47μF Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Package	Radial, Can
Tolerance ±20% Voltage - Rated 16V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1500 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Heigh - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Raistance) 1500 Hrs @ 85°C Ceneral Purpose 59mA @ 120Hz	Series	097 RLP 7
Voltage - Rated16VESR (Equivalent Series Resistance)-Lifetime @ Temp.1500 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency59mA @ 120HzRipple Current - High Frequency-Impedance3.5 OhmsLead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Fipple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Frequency Fipple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 1500 Hrs @ 85°C -40°C ~ 85°C Follows General Purpose 59mA @ 120Hz 59mA @ 120Hz 1000	Voltage - Rated	16V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency SymA @ 120Hz Ripple Current - High Frequency Impedance Syacing 10.197" (5.00mm) Size / Dimension 10.248" Dia (6.30mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Rapilar -40°C ~ 85°C -40°C ~ 85°C Reneral Purpose General Purpose 59mA @ 120Hz - 0.197" (5.00mm) - 0.248" Dia (6.30mm) Through Hole Radial, Can	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 59mA @ 120Hz Ripple Current - High Frequency - Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Lifetime @ Temp.	1500 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency Fipple Current - High Frequency Impedance Johns Lead Spacing Johns Lead Spacing Johns Lead Spacing Johns Johns Lead Spacing Johns Jo	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Polarization	Polar
Ripple Current - High Frequency Impedance 3.5 Ohms Lead Spacing 0.197" (5.00mm) Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Applications	General Purpose
Impedance3.5 OhmsLead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	59mA @ 120Hz
Lead Spacing0.197" (5.00mm)Size / Dimension0.248" Dia (6.30mm)Height - Seated (Max)0.315" (8.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	-
Size / Dimension 0.248" Dia (6.30mm) Height - Seated (Max) 0.315" (8.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Impedance	3.5 Ohms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can	Lead Spacing	0.197" (5.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	Size / Dimension	0.248" Dia (6.30mm)
Mounting Type Through Hole Package / Case Radial, Can	Height - Seated (Max)	0.315" (8.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

MAL209735479E6 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

MAL209735479E6 Payment Methods



















MAL209735479E6 Shipping Methods













If you have any question about MAL209735479E6, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com