



## MAL210116224E3 Information

Heisener.com

Part Number MAL210116224E3

Manufacturer Vishay BC Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 220000UF 20% 25V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **MAL210116224E3 Specifications**

Manufacturer Part NumberMAL210116224E3ManufacturerVishay BC ComponentsCategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeries101 PHR-STCapacitance220000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)6 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20.2A @ 100HzRipple Current - High Frequency-Impedance5 mOhmsLead Spacing1.122" (28.50mm)Size / Dimension2.559" Dia (65.00mm)	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series 101 PHR-ST Capacitance 220000µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 6 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance S mOhms Lead Spacing  Capacitors Radial, Can - Screw Terminals Aluminum Electrolytic Capacitors Radial, Can - Screw Terminals  Aluminum Electrolytic Capacitors Radial, Can - Screw Terminals  Aluminum Electrolytic Capacitors Radial, Can - Screw Terminals  Each Space Terminals  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal PHR-ST  Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal PHR-ST  Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal PHR-ST  Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal Capacitors  Aluminum Electrolytic Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal PHR-ST  Echal Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Echal Capacitors  Aluminum Electrolytic Capacitors  Aluminum Electrolytic Capacitors  Echal Capacitors  Aluminum Electrolytic Capacitors  Echal Capacitors  Echal Capacitors  Aluminum Electrolytic Capacitors  Echal Capa	Manufacturer Part Number	MAL210116224E3
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeries101 PHR-STCapacitance220000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)6 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20.2A @ 100HzRipple Current - High Frequency-Impedance5 mOhmsLead Spacing1.122" (28.50mm)	Manufacturer	Vishay BC Components
PackageRadial, Can - Screw TerminalsSeries101 PHR-STCapacitance220000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)6 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20.2A @ 100HzRipple Current - High Frequency-Impedance5 mOhmsLead Spacing1.122" (28.50mm)	Category	Capacitors
Series $101 \text{ PHR-ST}$ Capacitance $220000\mu\text{F}$ Tolerance $\pm 20\%$ Voltage - Rated $25\text{V}$ ESR (Equivalent Series Resistance) $6 \text{ mOhm @ 100Hz}$ Lifetime @ Temp. $15000 \text{ Hrs @ 85°C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency $20.2 \text{A @ 100Hz}$ Ripple Current - High Frequency-Impedance $5 \text{ mOhms}$ Lead Spacing $1.122^{\circ}$ (28.50mm)		Aluminum Electrolytic Capacitors
Capacitance220000μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)6 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency20.2A @ 100HzRipple Current - High Frequency-Impedance5 mOhmsLead Spacing1.122" (28.50mm)	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 25V  ESR (Equivalent Series Resistance) 6 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 20.2A @ 100Hz  Ripple Current - High Frequency -  Impedance 5 mOhms  Lead Spacing 1.122" (28.50mm)	Series	101 PHR-ST
Voltage - Rated  ESR (Equivalent Series Resistance)  6 mOhm @ 100Hz  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  5 mOhms  Lead Spacing  1.122" (28.50mm)	Capacitance	220000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  5 mOhms  Lead Spacing  1.122" (28.50mm)	Tolerance	±20%
Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  5 mOhms  Lead Spacing  15000 Hrs @ 85°C  -40°C ~ 85°C  -40°C	Voltage - Rated	25V
Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  5 mOhms  Lead Spacing  1.122" (28.50mm)	ESR (Equivalent Series Resistance)	6 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 20.2A @ 100Hz  Ripple Current - High Frequency -  Impedance 5 mOhms  Lead Spacing 1.122" (28.50mm)	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 5 mOhms Lead Spacing 1.122" (28.50mm)	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  5 mOhms  Lead Spacing  1.122" (28.50mm)	Polarization	Polar
Ripple Current - High Frequency - Impedance 5 mOhms Lead Spacing 1.122" (28.50mm)	Applications	General Purpose
Impedance 5 mOhms Lead Spacing 1.122" (28.50mm)	Ripple Current - Low Frequency	20.2A @ 100Hz
Lead Spacing 1.122" (28.50mm)	Ripple Current - High Frequency	-
	Impedance	5 mOhms
Size / Dimension 2.559" Dia (65.00mm)	Lead Spacing	1.122" (28.50mm)
	Size / Dimension	2.559" Dia (65.00mm)
Height - Seated (Max) 4.358" (110.70mm)	Height - Seated (Max)	4.358" (110.70mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Chassis Mount	Mounting Type	Chassis Mount
Package / Case Radial, Can - Screw Terminals	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

#### MAL210116224E3 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **MAL210116224E3 Payment Methods**





















### **MAL210116224E3 Shipping Methods**













If you have any question about MAL210116224E3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com